



Website



Facebook



Youtube

FENIXLIGHT LIMITED

Tel: +86-755-29631163/83/93 Fax: +86-755-29631181

Email: info@fenixlight.com www.fenixlight.com

Address: 8/Floor, Spring Valley, (Wonderful Life Wisdom Valley)
Meisheng Huigu Technology Industrial Park, 83 Dabao Road,
Bao'an District, Shenzhen 518133, China

Copy Right May. 2019 V2.0

All Rights Reserved By Fenixlight Limited

69.999.999.459-A2-20190624

FENIX
LIGHTING FOR EXTREMES

2019
PRODUCT CATALOG

To be the world's first outdoor sport lighting brands

FENIX
LIGHTING FOR EXTREMES



LIGHTING FOR EXTREMES

Founded in 2001, Fenix has developed into a China national high-tech enterprise, specializing in R&D, manufacturing and selling of mobile lighting tools, including flashlights, headlamps, bicycle lights, camping lanterns and lighting accessories. Fenix products are widely used in the following environments: outdoor sports, industrial, law enforcement, military, EDC (everyday carry), etc.

Fenix products are now being sold in more than 100 countries around the world, reaching tens of millions of users worldwide. Concentrating on development of LED lighting tools of high performance and reliability, Fenix has won recognition and praise from users for its excellent products and service. Fenix has become known worldwide as a premium LED lighting brand based on each product's excellent performance and reliable quality.

The best design is derived from the actual needs of users. Fenix aims to satisfy customers' pursuit of versatile, mobile lighting products. With the mission of "lighting for extremes", Fenix is committed to become the world's No.1 mobile lighting brand.

A person stands in a dark landscape at night, holding a flashlight that projects a powerful blue beam of light. The beam illuminates a large, leafy tree on the right and a dark mountain range in the background. The sky is filled with stars, and the overall scene is a mix of natural and artificial light.

ABOUT FENIX

BRAND ORIGIN

As the great Chinese thinker Lu Xun said: "Improvement roots from dissatisfaction". The establishment of Fenix also roots from dissatisfaction. A group of young men, passionate about high quality illumination tools but unsatisfied with lighting products at that time, set out to make perfect flashlights, endeavoring to make the best flashlights in the world.



Adhering to the concept of "providing excellent products to customers through innovative design", Fenix has grown up to become a world-renowned outdoor sport lighting brand!



BRAND CONNOTATION

The word Fenix roots from the English word phoenix [fi:niks], which in the Chinese translation means "phoenix" or "perfect thing", and the phoenix figure represents luck, blessedness and perfection in the Chinese culture.

FENIX'S AWARDS

- ★ Flashlight of 2005
- ★ National High - Tech Enterprise
- ★ The "Best in Show" Award in 2011 Outdoor Retailer Trade Show
- ★ The LD20 got the title: "Best LED Flashlight"
- ★ 2011 - 2013 "Zunlv Award" during annual election of Chinese outdoor industry awards
- ★ The "Best of Show" Award - AFTA Trade Show 2013
- ★ PD12 - ISPO "Award Winner" 2013/2014
- ★ Named: The Best Cycling Gear of 2013 by Outside magazine
- ★ CL20 - ISPO "Award Winner" 2015/2016
- ★ "Editor's Choice" award by Outdoor Life magazine
- ★ Single product "Brand of the Year" 2013
- ★ BT20 - ISPO Asia Products "Gold Winner" Award 2012/2013
- ★ Silver Prize in Asia Outdoor Industry Awards
- ★ Named "Best Bargain" by Backpacker magazine
- ★ Silver Prize in Chinese Outdoor Gear Award
- ★ Named as one of the "Top 10 Travel Gadgets under \$50" by New York Times newspaper
- ★ BC30R - Silver Award in Asia Outdoor Industry Awards; SPO Asia Products "Gold Winner" Award 2015/2016
- ★ CL25R - ISPO(Asia) Award Gold Winner
- ★ HL10 2016 - ISPO Global Product Winner
- ★ TK72R - Red Dot Award: Product Design 2017
- ★ TK35UE 2018 - Red Dot Award: Product Design 2018



 Waterproof	IP68
 Impact Resistance	1.5 m, 6 times

The IP Code, International Protection Marking, which consist of two digits.

The first digit indicates the level of protection that the enclosure provides against access to hazardous parts.

The second digit indicates the level of protection that the enclosure provides against harmful ingress of water.

First digit: Solid particle protection

0 : No protection against contact and ingress of objects

1 : >50 mm. Any large surface of the body, such as the back of a hand, but no protection against deliberate contact with a body part

2 : >12.5 mm. Fingers or similar objects

3 : >2.5 mm. Tools, thick wires, etc.

4 : >1 mm. Most wires, slender screws, large ants etc.

5 : Dust protected. Ingress of dust is not entirely prevented, but it must not enter in sufficient quantity to interfere with the satisfactory operation of the equipment.

6 : Dust tight. No ingress of dust; complete protection against contact (dust tight). A vacuum must be applied. Test duration of up to 8 hours based on air flow.

Second digit: Liquid ingress protection

0 : None

1 : Dripping water (vertically falling drops) shall have no harmful effect on the specimen when mounted in an upright position onto a turntable and rotated at 1 RPM.

2 : Dripping water when tilted at 15° Vertically dripping water shall have no harmful effect when the enclosure is tilted at an angle of 15° from its normal position. A total of four positions are tested within two axes.

3 : Spraying water. Water falling as a spray at any angle up to 60° from the vertical shall have no harmful effect, utilizing either: a) an oscillating fixture, or b) A spray nozzle with a counterbalanced shield. Test a) is conducted for 5 minutes, then repeated with the specimen rotated horizontally by 90° for the second 5-minute test. Test b) is conducted (with shield in place) for 5 minutes minimum.

4 : Splashing of water. Water splashing against the enclosure from any direction shall have no harmful effect, utilizing either: a) an oscillating fixture, or b) A spray nozzle with no shield. Test a) is conducted for 10 minutes. Test b) is conducted (without shield) for 5 minutes minimum.

5 : Water jets. Water projected by a nozzle (6.3 mm) against enclosure from any direction shall have no harmful effects.

6 : Powerful water jets. Water projected in powerful jets (12.5 mm nozzle) against the enclosure from any direction shall have no harmful effects.

7 : Immersion, up to 1 m depth. Ingress of water in harmful quantity shall not be possible when the enclosure is immersed in water under defined conditions of pressure and time (up to 1 m of submersion).

8 : Immersion, 1 m or more depth. The equipment is suitable for continuous immersion in water under conditions which shall be specified by the manufacturer. However, with certain types of equipment, it can mean that water can enter but only in such a manner that it produces no harmful effects. The test depth and duration is expected to be greater than the requirements for IPx7, and other environmental effects may be added, such as temperature cycling before immersion.

Drop test:

1.5 meters, 6 times : include top, bottom and any side - each for a test of twice.

INDEX

TACTICAL

TK series (TK65R, TK35UE, TK35, TK25UV, TK20R, TK16, TK15UE) ----- 13

Tough and powerful flashlights (patrolling, law enforcement, tactical)

PD series (UC35 V2.0, PD40R, PD35 V2.0, PD35TAC, PD32, PD25) ----- 21

Portable high-performance flashlights (military fans, policing, law enforcement)

T series (T5, T5Ti) ----- 25

Other military tools

OUTDOOR ACTIVITIES

LD series (LD42, LD22, LD15R, LD12, LD05 V2.0, LD02 V2.0, FD30) ----- 29

Professional outdoor flashlights (hiking, camping, climbing)

E series (UC30, E35UE, E30R, E25UE, E18R, E16Ti, E16, E15, E12, E05) ----- 33

EDC flashlights (Every Day Carry, compact and convenient)

S / SD series (SD20, SD11) ----- 39

Professional fields (diving, fishing, navigating)

HUNTING (FD41, TK32, TK25R&B, TK25 Red) ----- 43

SEARCH AND RESCUE ----- 47

(RC40, TK75, TK72R, TK47UE, TK47, LR40R) Long-range flashlights (searching, rescuing, patrolling)

HEADLAMPS

HP series (HP30R, HP25R, HP15UE) ----- 55

High-performance separated headlamps

HM series (HM 65R, HM50R, HM23, HL60R, HL55) ----- 56

All-metal high-performance integrated headlamps

HL series (HL40R, HL32R, HL30, HL26R, HL18R, HL15, HL12R) ----- 59

Lightweight outdoor headlamps

BICYCLE LIGHTS

BC series (BC35R, BC30R, BC30, BC25R, BC21R, BC05R) ----- 65

High-performance integrated bicycle lights

CAMPING LANTERNS

CL series (CL30R, CL26R, CL23, CL20R, CL09) ----- 73

High-performance camping lanterns

ACCESSORIES ----- 79

ACCESSORIES COMPATIBILITY GUIDE ----- 85

FENIX PRODUCTS SPECIFICATION CHART ----- 87

HIGH PERFORMANCE

Fenix utilizes the most advanced, world-class LED's with a lifespan of 50,000 hours, leading the trend in the LED industry and staying up to date with development in the LED industry. Owing to the accumulative experience of the diligent R&D team, Fenix is able to make the most of high photoelectric conversion efficiency, to have limited electric energy transformed into light energy, plus the choice of professional ultra-clear glass lens with anti-reflective coating, so that each spectral LED is effectively emitted. Additionally, outstanding constant current circuitry highlights Fenix's products, meaning a constant bright light with no flickering as the batteries discharge.

Digitally regulated output, constant brightness

Constant current circuit

HIGH RELIABILITY

Fenix abides by the ISO9001 quality control system, which strictly supervises material selection, product manufacturing and quality inspection. As a member of PLATO, Fenix always sticks with professional inspection equipment and conducts every test in accordance with ANSI standards. Reliable structure design empowers Fenix lighting tools with great heat dissipation, extra strong dust resistance and waterproof capability to face various environments. Most of Fenix's products are waterproof to IPX8 standard; the diving flashlight is even waterproof to 100 meters deep.

High-efficiency optical system

Latest LED

PROMINENT OPTICAL SYSTEM

Sparing no efforts in meeting different environmental conditions, Fenix focuses on light color and light spot design, thus making every Fenix product balanced in terms of output, distance and beam angle, and reliable enough for various demanding applications. Fenix continues searching for a breakthrough - some products have orange-peel reflectors for ideal lighting efficacy; some have dual light sources to allow for spot and floodlight needs; some even have composite reflectors for choosing multiple light colors. Fenix bicycle lights feature Dual Distance Beam System which is greatly favored by users and has received major industry awards.


Durable aircraft-grade aluminum

Premium type III hard-anodized anti-abrasive finish

IPX8 waterproofing treatment

EXQUISITE WORKMANSHIP

The application of advanced LED's and optical devices provide the foundation of manufacturing high-performance products. The critical fact that Fenix is greatly favored comes from manufacturing excellence and quality requirements. Fenix insists on aircraft-grade aluminum material to be produced by computerized numerical control (CNC) machinery, and premium Type III hard-anodized anti-abrasive finishing ensures Fenix products are sturdy and durable. Furthermore, exterior structure and surface processing is not the only end result. Fenix commits to excellence also in circuit design, an independent yet advanced SMT product line, CNC product line and oxygen installation, which all ensure that every product is refined internally as well as externally.



UNREMITTING INNOVATION

It is deeply believed that innovation is the source of the ongoing progress and development of the Fenix brand. On the one hand, Fenix has exploited the camping lantern, a new product line which enriches Fenix as an all-around outdoor lighting brand. On the other hand, Fenix is committed to developing and introducing new techniques, dedicated to pleasing illumination experience and user-friendliness. The four-proofing headlamps even lead the trend in high-performance headlamps, and the characteristic cold-resistant camping lantern act tough in harsh environments.

TACTICAL

TOUGH, PORTABLE AND HIGH-PERFORMANCE

- TK SERIES
TOUGH AND POWERFUL FLASHLIGHTS
- PD SERIES
PORTABLE HIGH-PERFORMANCE FLASHLIGHTS
- T SERIES
OTHER MILITARY TOOLS

Fenix Tactical series upholds the design concept of toughness, reliability and professionalism. This series enters with high performance and extended reach, which becomes the unmatched choice for policing, military activities and enforcing the law.





TK65R Max 3200 Lumens RECHARGEABLE SECURITY FLASHLIGHT



Technical innovation patent number:
ZL 201720063871.7
ZL 201721574627.3

- Patented catapult action belt clip
- High-performance and long-range
- Stainless steel strike bezel
- 7.2V/5000mAh Li-ion battery - 113 hours runtime
- Fast charging and battery level indication



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	3200 Lumens	1 h 45 min	375 m
HIGH	1000 Lumens	4 h 55 min	218 m
MED	400 Lumens	13 h 10 min	138 m
LOW	150 Lumens	35 h 45 min	83 m
ECO	30 Lumens	113 h	37 m
STROBE	3200 Lumens	/	/
SOS	400 Lumens	/	/

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

Battery: 5,000mAh / 7.2V Li-ion battery pack
Size: 10.65" x 2.42" x 1.44" / 270.5 x 61.5 x 36.5mm
Weight: 14.74 oz / 418 g (excluding battery)



TK35 ULTIMATE EDITION Max 3200 Lumens PORTABLE DUAL MODES FLASHLIGHT



reddot design award
winner 2018

- Patented toggle switch
- Micro USB charging battery holder
- High-performance and long-range
- Battery level indication

Technical innovation
patent number:
ZL 201721574627.3

Battery: 2 x 18650
Size: 6.48" x 1.89" x 1.69" / 164.5 x 48 x 43 mm
Weight: 10.09 oz / 286 g (excluding battery)



ANSI/PLATO FL1					
MODE	OUTPUT	TACTICAL MODE	OUTDOOR MODE	RUNTIME	DISTANCE
TURBO	3200 Lumens	✓	✓	1 h 30 min	300 m
	2000 Lumens			2 h	233 m
HIGH	1000 Lumens	✓	✓	3 h 40 min	169 m
MED	350 Lumens			10 h 50 min	100 m
LOW	100 Lumens	✓	✓	38 h 40 min	55 m
ECO	20 Lumens			152 h	20 m
STROBE	3200 Lumens	✓	✓	/	/
SOS	100 Lumens	✓	✓	/	/
				/	/

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

TK35 Max 1300 Lumens PORTABLE FAR-REACHING FLASHLIGHT



"Zunlv Award" of
the Year 2011




Best in Show Awards
in the Outdoor Retailer
trade show 2011



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

- Tactical dual switches
- 480 meters far-reaching distance
- Micro USB charging battery holder
- 235 hours long-lasting runtime



ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1300 Lumens	3 h 10 min	480 m
HIGH	500 Lumens	5 h 45 min	294 m
MED	150 Lumens	21 h 30 min	161 m
LOW	50 Lumens	68 h 15 min	97 m
ECO	10 Lumens	235 h	39 m
STROBE	1300 Lumens	/	/
SOS	50 Lumens	/	/

Battery: 2 x 18650
Size: 6.26" x 1.89" x 1.69" / 159 x 48 x 43 mm
Weight: 9.56 oz / 271 g (excluding battery)

TK25 UV Max 1000 Lumens DUAL LIGHTS LAW ENFORCEMENT FLASHLIGHT

- Patented dual lighting modes
- Patented technique of dual lightingsources switching
- Patented tactical dual tail switches
- High-efficiency UV light



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

Technical innovation
patent number:
ZL 201620457445.7
ZL 201620448074.6
ZL 201420489142.4

Battery: 1 x 18650 / 2 x CR123A
Size: 5.61" x 1.57" x 1" / 142.6 x 40 x 25.4 mm
Weight: 5.52 oz / 156.5 g(excluding battery)

ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h	225 m
HIGH	300 Lumens	5 h 20 min	124 m
MED	100 Lumens	22 h 20 min	75 m
LOW	15 Lumens	110 h	25 m
UV	3000 mW Lumens	6 h25 min	/
STROBE	1000 Lumens	/	/

TK20R Max 1000 Lumens DUAL TAIL SWITCHES TACTICAL FLASHLIGHT

- Patent plugging and charging technique
- Tactical dual tail switches
- Micro USB charging
- Inner waterproofing treatment
- Battery level indication



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

Technical innovation
patent number:
ZL 201620251620.7

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.96" x 1.34" x 1" / 151.5 x 34 x 25.4 mm
WEIGHT: 4.97 oz / 141 g (excluding battery)

ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME		DISTANCE
		3500 mA h	2900 mA h	
TURBO	1000 Lumens	2 h	1 h 40 min	310 m
HIGH	350 Lumens	4 h20 min	4 h	193 m
MED	150 Lumens	11 h	10 h 30 min	126 m
LOW	10 Lumens	160 h	135 h	31 m
STROBE	1000 Lumens	/	/	/



TK16 Max **1000** Lumens
TACTICAL DUAL TAIL SWITCHES

- Patented tactical dual switches
- Instant strobe
- Four output levels
- Tough strike bezel

Technical innovation
patent number:
ZL 201420489142.4

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.51" x 1.34" x 1" / 140 x 34 x 25.4 mm
WEIGHT: 4.30 oz / 122g (excluding battery)



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	1 h10 min	240 m
HIGH	400 Lumens	3 h25 min	155 m
MED	150 Lumens	10 h	97 m
LOW	10 Lumens	150 h	23 m
STROBE	1000 Lumens	/	/

TK15 **ULTIMATE EDITION** Max **1000** Lumens
FAR-REACHING TACTICAL FLASHLIGHT

- 325 meters far-reaching distance
- Dual switches for convenient operation
- Tactical switch for instant activation
- Stainless strike bezel

Technical innovation
patent number:
ZL 200920131945.1

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.61" x 1.34" x 1" / 142.5 x 34 x 25.4 mm
WEIGHT: 4.97 oz / 141 g (excluding battery)



Black
Gun grey

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h	325 m
HIGH	350 Lumens	4 h 20 min	194 m
MED	150 Lumens	11 h 30 min	125 m
LOW	10 Lumens	135 h	31 m
STROBE	1000 Lumens	/	/



UC35 **V2.0** Max **1000** Lumens
USB RECHARGEABLE TACTICAL FLASHLIGHT

- Patented plugging and charging technique
- Inner waterproofing treatment for the charging port
- Tactical tail switch for instant activation
- Dual switches control
- Boot-up battery level indication



Technical innovation
patent number:
ZL 201721611084.8

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.51"x 1" x 0.93" / 140 x 25.4 x 23.5 mm
WEIGHT: 3.14 oz / 89 g (excluding battery)

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h 15 min	266 m
HIGH	350 Lumens	4 h 10 min	160 m
MED	150 Lumens	10 h 40 min	98 m
LOW	50 Lumens	28 h 10 min	64 m
MOONLIGHT	1 Lumens	800 h	10 m
STROBE	1000 Lumens	/	/

PD40R Max **3000** Lumens
MICRO USB RECHARGEABLE PORTABLE FLASHLIGHT

- Inner waterproofing treatment
- Micro USB charging
- Dual switch operation
- Lockout function
- Battery level indication



Waterproof	IP68
Impact Resistance	1.5 m, 6 times



Battery: 1 x 26650 Li-ion power battery
Size: 5.45" x 1.34" x 1.18" / 138.5 x 34 x 30 mm
Weight: 4.44 oz / 126 g(excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	3000 Lumens	12 min	200 m
HIGH	1000 Lumens	2 h	123 m
MED	350 Lumens	7 h25 min	68 m
LOW	100 Lumens	21 h15 min	39 m
ECO	20 Lumens	55 h	16 m
STROBE	1000 Lumens	/	/
SOS	350 Lumens	/	/



PD35 V2.0 Max 1000 Lumens PORTABLEHIGH-PERFORMANCE FLASHLIGHT


NEW



The "Best of Show" Award - AFTA Trade Show 2013



- 250 meters far-reaching beam distance
- Pocket-sized for convenient carry
- Dual switches for separate control
- Battery level indication
- Two colors for option



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h 50 min	250 m
HIGH	350 Lumens	5 h 10 min	157 m
MED	150 Lumens	12 h 25 min	103 m
LOW	50 Lumens	29 h 30 min	60 m
ECO	3 Lumens	430 h	13 m
STROBE	1000 Lumens	/	/


Battery: 1 x 18650 / 2 x CR123A
Size: 5.47" x 1" x 0.91" / 139 x 25.4 x 22.7 mm
Weight: 3.07 oz / 87 g (excluding battery)

PD35 TACTICAL EDITION Max 1000 Lumens DUAL MODES MULTIPURPOSE TACTICAL FLASHLIGHT



- Outdoor and tactical modes for varied scenes
- Compact size with 1000 lumens high performance

Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1					
MODE	OUTPUT	TACTICAL MODE	OUTDOOR MODE	RUNTIME	DISTANCE
TURBO	1000 Lumens	✓	✓	1 h 10 min	200 m
HIGH	500 Lumens	✓	✓	2 h 55 min	135 m
MED	200 Lumens	✓	✓	8 h 30 min	80 m
LOW	60 Lumens	✓	✓	29 h 15 min	48 m
ECO	8 Lumens			140 h	17 m
STROBE	1000 Lumens	✓	✓	/	/

BATTERY: 1*18650 / 2*CR123A
SIZE: 5.39" x 1" x 0.89" / 137 x 25.4 x 22.7 mm
WEIGHT: 3.14 oz / 89 g (excluding battery)



PD32 Max **900** Lumens
HIGH-PERFORMANCE
POCKET-SIZED
FLASHLIGHT

- Compact and lightweight
- 240 meters far-reaching beam distance
- Dual switches for separate control
- 260 hours long-lasting runtime



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.10" x 0.94" x 0.89" / 129.5 x 24 x 22.6 mm
WEIGHT: 2.72 oz / 77 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	900 Lumens	1 h55 min	240 m
HIGH	400 Lumens	4 h	156 m
MED	150 Lumens	10 h25 min	97 m
LOW	50 Lumens	37 h5 min	52 m
ECO	5 Lumens	260 h	13 m
STROBE	900 Lumens	/	/
SOS	50 Lumens	/	/

PD25 Max **550** Lumens
TACTICAL COMPACT
FLASHLIGHT

- Dual switches for separate control
- Compact for convenient carry



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x 16340 / 2 x CR123A
SIZE: 3.66" x 0.85" x 0.85" / 93 x 21.5 x 21.5 mm
WEIGHT: 1.66 oz / 47 g (excluding battery)

ANSI/PLATO FL1						
MODE	OUTPUT		RUNTIME		DISTANCE	
	CR123A	16340	CR123A	16340	CR123A	16340
TURBO	400 Lumens	550 Lumens	1 h10 min	35 min	116 m	130 m
HIGH	150 Lumens	150 Lumens	3 h15 min	2 h25 min	71 m	
MED	50 Lumens	50 Lumens	9 h5 min	7 h10 min	41 m	
LOW	5 Lumens	5 Lumens	100 h	53 h	13 m	
STROBE	400 Lumens	550 Lumens	/	/	/	

T5Ti HALBERD

TITANIUM TACTICAL PEN



Technical innovation
patent number:
ZL 201630526252.8

- Tungsten steel hard alloy strike bezel
- Germany SchneiderSchmidt P950M pressurized pen refill
- TC4 Titanium alloy pen body
- Three color options

✓ Impact Resistance	1.5 m, 6 times
---------------------	----------------

Size: 5.45" x 0.49" / 138.5 x 12.5 mm
 Net Weight: 1.41 oz / 40 g
 Strike bezel material: Tungsten steel hard alloy
 Three color options: Space grey, Storm blue, Aurora purple



Up-close defense



Tactical attack



Emergency escape

T5 HALBERD

ALUMINUM TACTICAL PEN



Technical innovation
patent number:
ZL 201630526252.8

- Tungsten steel hard alloy strike bezel
- Germany Schneiderpremium pen refill
- Aluminum alloy pen body

✓ Impact Resistance	1.5 m, 6 times
---------------------	----------------

Size: 5.45" x 0.49" / 138.5 x 12.5 mm
 Weight: 1.41 oz / 40 g
 Strike bezel material: Tungsten steel hard alloy



OUTDOOR ACTIVITIES

RELIABLE AND PROFESSIONAL OUTDOOR FLASHLIGHTS

- **LD SERIES**
PROFESSIONAL OUTDOOR FLASHLIGHTS
- **E SERIES**
EVERYDAY CARRY FLASHLIGHTS
- **S SERIES**
PROFESSIONAL FIELDS

Fenix Outdoor series flashlights are professional lighting tools that specially designed for a variety of outdoor environments. Its ingenious design, excellent performance and high reliability in water and impact resistance mean that you won't have to worry and compromise when diving and other special activities, you only need to trust the safe and long-lasting lighting pet.



LD42 Max 1000 Lumens
ROTARY NECK FLASHLIGHT

- Patented rotary neck technique
- Compact size with 1000 lumens high performance
- Max 350 meters beam distance
- 4 AA batteries



NEW



Technical innovation patent number:
ZL 201821227065.X
ZL 201821227062.6

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	1 h 10 min	350 m
HIGH	350 Lumens	2 h 38 min	190 m
MED	100 Lumens	13 h 10 min	125 m
LOW	50 Lumens	36 h 40min	72 m
ECO	5 Lumen	130 h 20min	23 m

BATTERY: 4 x AA
SIZE: 6.28" x 1.34" x 1.28" / 159.5 x 34 x 32.5 mm
WEIGHT: 3.28 oz / 93 g (excluding battery)

LD22 Max 300 Lumens
2AA MULTIFUNCTIONAL
OUTDOOR FLASHLIGHT

- Tactical tail switch and stainless side switch
- Powered by 2 AA batteries
- 4 output levels and 2 flash modes
- Tactical tail switch for instant activation
- Stainless steel light head



Technical innovation patent number:
ZL 201530133371.2

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Alkaline	Ni-MH	
TURBO	300 Lumens	40 min	1 h 25 min	120 m
HIGH	100 Lumens	5 h 5 min	7 h 10 min	71 m
MED	30 Lumens	22 h 30 min	25 h 5 min	40 m
LOW	5 Lumens	90 h	100 h	14 m
STROBE	300 Lumens	/	/	/
SOS	100 Lumens	/	/	/

BATTERY: 2 x AA
SIZE: 6.10" x 0.85" x 0.72" / 155 x 21.5 x 18.3 mm
WEIGHT: 2.54 oz / 72 g (excluding battery)

LD15R Max 500 Lumens
MULTIPURPOSE
RECHARGEABLE
FLASHLIGHT

- Micro USB charging
- Battery level indication
- Red and white lighting sources
- Magnetic tail - hands-free fixation
- Stainless steel two-way body clip



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x 16340 / 1 x CR123A
SIZE: 2.76" x 0.87" x 0.75" / 70 x 22 x 19 mm
WEIGHT: 1.41 oz / 40 g (excluding battery)

ANSI/PLATO FL1				
WHITE LIGHT	MODE	OUTPUT	RUNTIME	DISTANCE
	TURBO	500 Lumens	1 h 20 min	85 m
	HIGH	150 Lumens	2 h 50 min	46 m
	MED	30 Lumens	13 h 20 min	23 m
RED LIGHT	MODE	OUTPUT	RUNTIME	DISTANCE
	LOW	3 Lumens	110 h	6 m
	RED	4 Lumens	30 h	5 m
	SIGNAL LIGHT	4 Lumens	/	/
	SOS	4 Lumens	/	/

LD12 Max 320 Lumens
1 AA TACTICAL
ULTRA-COMPACT
FLASHLIGHT

- Compact for easy carry
- Powered by one AA battery
- Dual switches for separate control
- Instant strobe



Technical innovation patent number:
ZL 201530133371.2

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x 14500 / 1 x AA
SIZE: 4.04" x 0.85" x 0.81" / 102.5 x 21.5 x 20.5 mm
WEIGHT: 1.98 oz / 56 g (excluding battery)

ANSI/PLATO FL1						
MODE	OUTPUT		RUNTIME		DISTANCE	
	Alkaline/Ni-MH	14500	Alkaline	Ni-MH	14500	
TURBO	150 Lumens	320 Lumens	50 min	1 h 45 min	1 h	94 m/135 m
HIGH	70 Lumens		3 h	5 h 40 min	3 h 30 min	67 m
MED	30 Lumens		9 h 40 min	13 h	11 h	45 m
LOW	5 Lumens		40 h	60 h	50 h	18 m
STROBE	150 Lumens	320 Lumens	/	/	/	/

LD05 **v2.0** Max 100 Lumens
DUAL LIGHTING SOURCES
WORKING PENLIGHT

- Warm white for better color rendering
- UV light for fluorescer detection
- One-handed stainless steel tail switch
- Powered by 2 AAA batteries
- Pen-shaped design, compact and convenient



NEW

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 2 X AAA
SIZE: 5.31" x 0.53" x 0.53" / 135 x 13.5 x 13.5 mm
WEIGHT: 1.05 oz / 29.7 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Alkaline	Ni-MH	
HIGH	100 Lumens	1 h 40 min	2 h 10 min	54 m
MED	25 Lumens	7 h 50 min	6 h 40 min	34 m
LOW	5 Lumens	70 h	36 h	27 m
UV	200mW	9 h	7 h	/



LD02 **v2.0** Max 70 Lumens
DUAL LIGHT SOURCES
EDC PENLIGHT

- Warm white for better color rendering
- UV light for fluorescer detection
- One-handed stainless steel tail switch
- Powered by 2 AAA batteries
- Pen-shaped design, compact and convenient



NEW

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x AAA
SIZE: 3.62" x 0.53" x 0.53" / 92 x 13.5 x 13.5 mm
WEIGHT: 0.85 oz / 24 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Alkaline	Ni-MH	
HIGH	70 Lumens	40 min	45 min	48 m
MED	25 Lumens	2 h 40 min	2 h 55 min	27 m
LOW	1 Lumens	75 h	45 h	6 m
UV	200mW	4 h	3 h	/

FD30 Max 900 Lumens
NEW STYLE 360°ROTARY
FOCUSING FLASHLIGHT

- Dual reflectors focusing technique
- Dual reflector optical systems
- Dual switches for separate operation
- Handy and compact



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

Technical innovation
patent number:
ZL 201120064435.4

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.53" x 1" x 0.91" / 140.5 x 25.4 x 23 mm
WEIGHT: 3.39 oz / 96 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
			SPOT	FLOOD
TURBO	900 Lumens	2 h	200 m	67 m
HIGH	350 Lumens	4 h 30 min	117 m	43 m
MED	150 Lumens	11 h	77 m	28 m
LOW	50 Lumens	40 h 30 min	44 m	16 m
ECO	8 Lumens	170 h	17 m	8 m
STROBE	900 Lumens	/	/	/

UC30 Max 1000 Lumens
USB RECHARGEABLE
ULTRA-COMPACT
FLASHLIGHT

- Handy and ultra-compact
- Micro USB charging
- 1000 lumens output
- One-switch control



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.12" x 1" x 0.92" / 130 x 25.4 x 23.4 mm
WEIGHT: 2.72 oz / 77 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	1 h 25 min	253 m
HIGH	350 Lumens	3 h 20 min	156 m
MED	150 Lumens	8 h 45 min	101 m
LOW	50 Lumens	28 h 25 min	58 m
ECO	5 Lumens	150 h	21 m
STROBE	1000 Lumens	/	/

E35 ULTIMATE EDITION Max 1000 Lumens
PORTABLE DUAL SWITCHES
FLASHLIGHT

- Handy and compact
- Dual switches for separate control
- Lockout function avoids accidental activation



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	1 h 50 min	160 m
HIGH	450 Lumens	4 h	106 m
MED	150 Lumens	11 h 50 min	61 m
LOW	50 Lumens	42 h 30 min	37 m
ECO	8 Lumens	150 h	14 m
STROBE	1000 Lumens	/	/
SOS	150 Lumens	/	/

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 4.80" x 0.94" x 0.91" / 122 x 24 x 23 mm
WEIGHT: 2.54 oz / 72 g (excluding battery)

E30R Max 1600 Lumens
COMPACT BUT
HIGH-PERFORMANCE
RECHARGEABLE
FLASHLIGHT

- Patented automobile type optical lens coating process for clearer vision
- Compact size but with 1600 lumens output
- Magnetic charging
- Three ways of avoiding accidental activation
- One-switch control
- Battery level indication



NEW

Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1600 Lumens	1 h 27 min	203 m
HIGH	800 Lumens	4 h 55 min	150 m
MED	350 Lumens	5 h 28 min	93 m
LOW	150 Lumens	17 h 32 min	62 m
ECO	30 Lumens	70 h 30 min	27 m
STROBE	1600 Lumens	/	/

BATTERY: 1 x 18650 / 2 x CR123A
Size: 3.86" x 1" x 0.85" / 98 x 25.4 x 21.5 mm
WEIGHT: 1.80 oz / 51 g (excluding battery)

E25 ULTIMATE EDITION Max 900 Lumens
2AA DUAL SWITCHES
FLASHLIGHT

- Dual switches for separate control
- Lockout function avoids accidental activation
- Intelligent drive circuit



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1						
MODE	OUTPUT		RUNTIME			DISTANCE
	Alkaline/Ni-MH	14500	Ni-MH	Alkaline	14500	
TURBO	/ 1000 Lumens		/ 50 min			200 m
HIGH	350 Lumens		1 h 30 min	50 min	2 h 15 min	112 m
MED	160 Lumens		4 h 35 min	2 h 10 min	5 h 5 min	76 m
LOW	50 Lumens		13 h 25 min	13 h 10 min	16 h 30 min	43 m
ECO	5 Lumens		100 h	90 h	95 h	13 m
STROBE	350 Lumens	1000 Lumens	/	/	/	/
SOS	160 Lumens		/	/	/	/

BATTERY: 2 x 14500 / 2 x AA
SIZE: 6.34" x 1" x 0.78" / 161 x 25.4 x 19.6 mm
WEIGHT: 3.07 oz / 87 g (excluding battery)

E18R Max 750 Lumens
ULTRA-COMPACT
HIGH-PERFORMANCE
RECHARGEABLE EDC
FLASHLIGHT

- Patented automobile type optical lens coating process
- Magnetic charging
- Battery level indication
- Three ways against accidental activation
- Magnetic tail - eliminates hand fatigue



NEW

Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	750 Lumens	45 min	136 m
HIGH	150 Lumens	2 h 35 min	58 m
MED	30 Lumens	13 h 30 min	25 m
LOW	5 Lumens	70 h	14 m
STROBE	750 Lumens	/	/

Technical innovation patent number:
ZL 201820183805.8
ZL 201810103796.1

BATTERY: ARB-L16-700P / 1 x CR123A
SIZE: 2.36" x 0.83" x 0.79" / 60 x 21 x 20 mm
WEIGHT: 1.16 oz / 33 g (excluding battery)



E16Ti Max 650 Lumens

COLLECTION EDITION TITANIUM EDC FLASHLIGHT

NEW



- Patented automobile type optical lens coating process for clearer vision
- Two-color oxidation finish; ambilight and unique
- Titanium alloy - corrosion and temperature resistance
- Two ways of avoiding accidental activation
- Two-way body clip

Technical innovation
patent number:
ZL 201820183805.8
ZL 201810103796.1

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	650 Lumens	1 h 36 min	131 m
HIGH	150 Lumens	2 h 18 min	62 m
MED	30 Lumens	11 h	27 m
LOW	3 Lumens	60 h	7 m

BATTERY: 1 x 16340 / 1 x CR123A
SIZE: 2.01" x 0.83" x 0.78" / 51 x 20.9 x 19.7 mm
WEIGHT: 0.74 oz / 21 g (excluding battery)



E16 Max 700 Lumens

MINI SIZE HIGH-PERFORMANCE EDC FLASHLIGHT

NEW

- Patented automobile type optical lens coating process for clearer vision
- Neutral white light for better color rendering
- Two ways of avoiding accidental activation
- Magnetic tail - eliminates hand fatigue
- Two-way stainless steel body clip



Technical innovation
patent number:
ZL 201820183805.8
ZL 201810103796.1

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1

MODE	OUTPUT		RUNTIME		DISTANCE	
	16340	CR123A	16340	CR123A	16340	CR123A
TURBO	700 Lumens	300 Lumens	1 h 5 min	1 h 55 min	142 m	93 m
HIGH	150 Lumens	150 Lumens	2 h	2 h 50 min	66 m	
MED	30 Lumens	30 Lumens	11 h 55 min	25 h	31 m	
LOW	3 Lumens	3 Lumens	70 h	110 h	13 m	
STROBE	700 Lumens	300 Lumens	/	/	/	

BATTERY: 1 x 16340 / 1 x CR123A
SIZE: 2.01" x 0.83" x 0.78" / 51 x 21.1 x 19.8 mm
WEIGHT: 0.74 oz / 21 g (excluding battery)

E15 Max 450 Lumens

MINI SIZE EDC FLASHLIGHT

- Mini size and light weight
- One-handed operation



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1

MODE	OUTPUT		RUNTIME		DISTANCE	
	16340	CR123A	16340	CR123A	16340	CR123A
HIGH	450 Lumens	270 Lumens	55 min	1 h 35 min	132 m	91 m
HIGH	110 Lumens		3 h 15 min	5 h 5 min	58 m	
MED	50 Lumens		9 h 25 min	12 h 30 min	38 m	
LOW	8 Lumens		40 h	72 h	15 m	

BATTERY: 1 x 16340 / 1 x CR123A
SIZE: 2.55" x 0.87" x 0.75" / 64.8 x 22 x 19 mm
WEIGHT: 1.02 oz / 29 g (excluding battery)

E12 Max 130 Lumens
MINI PORTABLE EDC
FLASHLIGHT



- Mini size for easy carry
- Hanging hole for quick-release lanyard mounting and dismounting
- Invaginated switch avoids accidental activation and for tail standing

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x AA
SIZE: 3.54" x 0.75" x 0.75" / 90 x 19 x 19 mm
WEIGHT: 1.01 oz / 28.5 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Ni-MH	Alkaline	
HIGH	130 Lumens	1 h 30 min	1 h	88 m
MED	50 Lumens	6 h 30 min	3 h 30 min	51 m
LOW	8 Lumens	40 h	22 h	19 m

E05 Max 85 Lumens
SUPER MINI EDC
FLASHLIGHT



- Mini size for easy carry
- Multiple colors for option

Waterproof	IP68
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x AAA
SIZE: 2.62" x 0.59" x 0.59" / 66.5 x 15 x 15 mm
WEIGHT: 0.44 oz / 12.5 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Ni-MH	Alkaline	
HIGH	85 Lumens	1 h	45 min	45 m
MED	25 Lumens	4 h 15 min	4 h 15 min	18 m
LOW	8 Lumens	15 h 30 min	15 h	8 m






SD11 Max 1000 Lumens

DIVING AND PHOTOGRAPHING FLASHLIGHT

- Submersible to 100 meters
- "R+" soft light for enhances natural color
- 110° super wide beam angle for even and soft lighting effect
- Magnetic rotating ring for one-handed operation
- Dual layers body structure; corrosion resistant



Waterproof	IP68
Impact Resistance	1.5 m, 6 times



Rotating magnetic ring for one-handed control
Twist the flashlight head to get access to three lighting modes and turn on/off the light.



Compatible with two 18650 Li-ion or four CR123A batteries

SD20 Max 1000 Lumens

MAGNETIC ROTARY DIVING FLASHLIGHT



Waterproof	IP68
Impact Resistance	1.5 m, 6 times


- 100 meters submersible
- Magnetic rotary ring for one-handed output selection
- White and red lights
- Floodlight for wide-range view
- Battery level indication

ANSI/PLATO FL1				
MODE		OUTPUT	RUNTIME	DISTANCE
WHITE LIGHT	HIGH	1000 Lumens	3 h	172 m
	LOW	400 Lumens	7 h 30 min	108 m
RED LIGHT		105 Lumens	8 h	73 m

BATTERY: 2 x 18650 / 4 x CR123A

SIZE: 8.19" x 1.57" x 1.02" / 208 x 40 x 26 mm

WEIGHT: 8.64 oz / 245 g (excluding battery)



BATTERY: 1 x 18650 / 2 x CR123A

SIZE: 5.43" x 1.34" x 1.02" / 138 x 34 x 26 mm

WEIGHT: 4.67 oz / 132.5 g (excluding battery)

ANSI/PLATO FL1				
MODE		OUTPUT	RUNTIME	DISTANCE
WHITE LIGHT	HIGH	1000 Lumens	2 h	45 m
	LOW	500 Lumens	3 h 40 min	30 m
R+		250 Lumens	3 h	23 m

"R+" is the optimal combination of neutral white light and red light, which is super fit for underwater viewing and photographing, since red light is extraordinarily scarce there even if you have enough brightness.

HUNTING

**FAR-REACHING,
HIGH-OUTPUT AND
MULTICOLORED**

Fenix hunting series features high output, optimal beam distance and reliable performance, in addition, equipped with multiple color sources and sufficient accessories, making this series a indispensable helper in night hunting, prey tracking and equipment inspection.



FD41 Max 900 Lumens
ROTARY FOCUSING
LONG-RANGE
FLASHLIGHT

- Patented focusing technique
- Dual switches
- Tactical switch
- 340 meters far-reaching distance

Technical innovation
patent number:
ZL 201220012628.X
ZL 201620760901.5
ZL 200920131945.1
ZL 201610575575.5

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.75" x 1.57" x 1" / 146 x 40 x 25.4 mm
WEIGHT: 5.64 oz / 160 g (excluding battery)



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
			SPOT	FLOOD
TURBO	900 Lumens	1 h 40 min	340 m	47 m
HIGH	350 Lumens	3 h 50 min	218 m	30 m
MED	150 Lumens	10 h 15 min	141 m	20 m
LOW	10 Lumens	150 h	37 m	6 m
STROBE	900 Lumens	/	/	/


TK32 Max 1000 Lumens
TRI-COLOR SOURCES
FAR-REACHING HUNTING
FLASHLIGHT

- Tri-color sources of white, red and green
- Dual tail switches
- Max 422 meters far-reaching beam distance
- Max 170 hours long runtime

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 6.26" x 2.05 x 1" / 159 x 52 x 25.4 mm
WEIGHT: 6.17 oz / 175 g (excluding battery)



Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	1 h 50 min	422 m
HIGH	350 Lumens	4 h 45 min	245 m
MED	100 Lumens	15 h 25 min	138 m
LOW	8 Lumens	170 h	40 m
RED HIGH	105 Lumens	4 h 15 min	65 m
RED LOW	15 Lumens	65 h	23 m
GREEN HIGH	165 Lumens	5 h 30 min	105 m
GREEN LOW	30 Lumens	40 h	45 m

TK25 R&B Max 1000 Lumens
MULTI-COLORED HUNTING
FLASHLIGHT

- Patented technique of rotary mode selection switching
- Patented dual lighting modes
- Patented tactical dual tail switches
- White, red and blue light sources
- Free rotary switching between white, red and blue lights

Technical innovation
patent number:
ZL 201620457445.7
ZL 201420489142.4

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.61" x 1.57" x 1" / 142.6 x 40 x 25.4 mm
WEIGHT: 5.52 oz / 156.5 g (excluding battery)



Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h	225 m
HIGH	300 Lumens	5 h 20 min	124 m
MED	100 Lumens	22 h 20 min	75 m
LOW	15 Lumens	110 h	25 m
RED HIGH	150 Lumens	7 h 30 min	132 m
RED LOW	25 Lumens	40 h	49 m
BLUE	60 Lumens	6 h 40 min	41 m
STROBE	1000 Lumens	/	/

TK25 Red Max 1000 Lumens
DUAL LIGHTING SOURCES
HUNTING FLASHLIGHT

- Patented dual lighting modes
- Patented technique of rotary mode selection switching
- Patented tactical dual tail switches
- 5500mW high-efficiency red light, 200 meters beam distance
- 1000 lumens high-performance white light, for pre- and after hunting checking

Technical innovation
patent number:
ZL 201620457445.7
ZL 201420489142.4

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 5.61" x 1.57" x 1" / 142.6 x 40 x 25.4 mm
WEIGHT: 5.52 oz / 156.5 g (excluding battery)



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
WHITE LIGHT	TURBO	1000 Lumens	2 h
	HIGH	300 Lumens	5 h 20 min
	MED	100 Lumens	22 h 20 min
	LOW	15 Lumens	110 h
	STROBE	1000 Lumens	/
RED LIGHT	HIGH	310 Lumens/5500mW	2 h 35 min
	MED	100 Lumens/1200mW	9 h 20 min
	LOW	10 Lumens/90mW	100 h

SEARCH & RESCUE

SEARCHING, RESCUING, PATROLLING AND CAVING FLASHLIGHTS

Fenix Searching&Rescuing series combines ultra-high performance with user-friendly design. Its ultra-high output and far-reaching beam distance provide excellent lighting support for searching and rescuing activities, plus reliable design of water, dust and impact resistance. This tough series must be a irreplaceable lighting tool for outdoor searching and rescuing.






RC40 Max 6000 Lumens

SUPER BRIGHT RECHARGEABLE SEARCHING FLASHLIGHT



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

- Max 730 meters long-range beam distance
- Charging and discharging function
- Tailored 7.2V/7800mAh Li-ion battery pack, 125 hours runtime
- Battery level indication



ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	6000 Lumens	1 h	730 m
HIGH	4000 Lumens	1 h 50 min	633 m
MED	2000 Lumens	4 h 5 min	444 m
LOW	500 Lumens	18 h 15 min	221 m
ECO	45 Lumens	125 h	58 m
STROBE	6000 Lumens	/	/
SOS	500 Lumens	/	/

BATTERY: Tailored 7.2V/7800mAh Li-ion battery pack
SIZE: 10.71" x 4.25" x 2.05" / 272 x 108 x 52 mm
WEIGHT: 43.53 oz / 1234 g (excluding battery)




TK75 Max 5100 Lumens

SUPER BRIGHT MULTIFUNCTIONAL FLASHLIGHT



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

- Max 850 meters beam distance
- Micro USB charging
- Battery level indication
- Stainless steel strike bezel



BATTERY: 4 x 18650
SIZE: 7.40" x 3.39" x 2.09" / 188 x 86 x 53 mm
WEIGHT: 20.28 oz / 575 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	5100 Lumens	2 h 15 min	850 m
HIGH II	2000 Lumens	3 h	517 m
HIGH I	1000 Lumens	6 h	367 m
MED	450 Lumens	17 h 45 min	257 m
LOW	150 Lumens	46 h	147 m
ECO	50 Lumens	95 h	85 m
STROBE	5100 Lumens	/	/
SOS	150 Lumens	/	/



TK72R Max 9000 Lumens

SUPER BRIGHT SMART FLASHLIGHT



Waterproof	IP68
Impact Resistance	1.5 m, 6 times

- OLED digital screen displays: output, runtime, battery status
- Micro USB charging
- USB discharging - power bank function
- Three switches in the neck - easy and fast operation
- Instant Turbo



BATTERY: 7.2V/7000mAh Li-ion battery pack
SIZE: 6.14" x 2.32" x 1.97" / 156 x 59 x 50 mm
WEIGHT: 14.53 oz / 412 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
HIGH	9000 Lumens	50 min	286 m
LOW	100 Lumens	50 h	31 m
STROBE	4000 Lumens	/	/

TK47 ULTIMATE EDITION Max 3200 Lumens

DUAL-PURPOSE HIGH-PERFORMANCE FLASHLIGHT



- Patented separately controlled head- and tail light sources
- Multifunctional tail light for relaxing, reading, camping or signaling
- Two independent light switches feature lockout function
- Stainless steel strike bezel

BATTERY: 2 x 18650
SIZE: 10.48" x 2.42" x 1.13" / 266.2 x 61.5 x 28.6 mm
WEIGHT: 12.87 oz / 365 g(excluding battery)

Technical innovation patent number:
 ZL 201620837225.7

Waterproof	IP68
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1				
	MODE	OUTPUT	RUNTIME	DISTANCE
HEAD	TURBO	3200 Lumens	1 h	408 m
	HIGH	1000 Lumens	3 h 20 min	232 m
	MED	350 Lumens	11 h 20 min	130 m
	LOW	100 Lumens	46 h	69 m
	ECO	20 Lumens	170 h	31 m
	STROBE	3200 Lumens	/	/
TAIL	WHITE	30 Lumens	43 h 30 min	*8 m
	RED	1.5 Lumens	150 h	/
	RED FLASH	1.5 Lumens	/	/
	RED SOS	1.5 Lumens	/	/

*Tail light with a wide-range 8m beam diameter





TK47 Max **1300** Lumens
**DUAL-PURPOSE LONG-RANGE
FLASHLIGHT**



- Patented separately controlled head- and tail light sources
- Max 700 meters beam distance
- Multifunctional tail light for relaxing, reading, camping or signaling
- Two independent light switches feature lockout function
- Stainless steel strike bezel

BATTERY: 2 x 18650
SIZE: 10.48" x 2.42" x 1.13" / 266.2 x 61.5 x 28.6 mm
WEIGHT: 13.26 oz / 376 g (excluding battery)

Technical innovation
patent number:
ZL 201620837225.7

 Waterproof	IP68
 Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
HEAD	TURBO	1300 Lumens	1 h 50 min	700 m
	HIGH	400 Lumens	7 h 15 min	412 m
	MED	100 Lumens	40 h	214 m
	LOW	10 Lumens	220 h	73 m
	STROBE	1300 Lumens	/	/
TAIL	WHITE	30 Lumens	43 h 30 min	*8 m
	RED	1.5 Lumens	150 h	/
	RED FLASH	1.5 Lumens	/	/
	RED SOS	1.5 Lumens	/	/

*Tail light with a wide-range 8m beam diameter

LR40R Max **12000** Lumens
**HIGH-PERFORMANCE RECHARGEABLE
ULTRA-COMPACT SEARCHING FLASHLIGHT**



- 773 meters long-range beam distance
- Spot- and floodlight modes
- Type-C fast charging interface
- USB discharging - power bank function
- Battery level indication

BATTERY: 4 x 18650 battery pack
SIZE: 6.06" x 3.15" x 2" / 154 x 80 x 51 mm
WEIGHT: 17.64 oz / 500 g (excluding battery)

NEW

 Waterproof	IP68
 Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
SPOT	HIGH	1000 Lumens	7 h	640 m
	MED	350 Lumens	22 h 30 min	401 m
	LOW	150 Lumens	44 h 31 min	263 m
	ECO	50 Lumens	92 h 18 min	163 m
FLOOD	TURBO	11000 Lumens	45 min	410 m
	HIGHI	6000 Lumens	2 h	295 m
	HIGHII	3000 Lumens	2 h 50 min	200 m
	MED	1000 Lumens	7 h 15 min	115 m
	LOW	350 Lumens	22 h 44 min	65 m
	STROBE	3000 Lumens	/	/
	SOS	350 Lumens	/	/

HEADLAMPS

■ HP SERIES

HIGH-PERFORMANCE SEPARATED HEADLAMPS

■ HM SERIES

ALL-METAL HIGH-PERFORMANCE INTEGRATED HEADLAMPS

■ HL SERIES

LIGHTWEIGHT OUTDOOR HEADLAMPS

Taking full advantage of modern lighting technology and creative design, Fenix successfully develops the headlamp series with outstanding performance that competes in extreme environments. The headlamps cover integrated, separate type and light weight, by using metal housing and constant brightness regulation circuit, Fenix headlamp series produces much brighter beam and offers more functions, longer runtime and better durability compared to the competitors. The Fenix headlamp models will satisfy your various lighting needs when running, camping, hiking, caving, cycling, searching, mountaineering, etc.



HP30R Max 1750 Lumens
HIGH-PERFORMANCE
PROFESSIONAL
HEADLAMP

- Patented innovative lamp holder
- Spot- and floodlights, 90° wide beam angle, 202 meters beam distance
- Dual switches for separate control
- Charging and discharging function

Technical innovation
patent number:
ZL 201120016782.X
ZL 201020582158.1

BATTERY: 2 x 18650 / 4 x CR123A
SIZE: Lamp head: 3.03" x 2.05" x 1.34" / 77 x 52 x 34 mm
Battery case: 4.53" x 2.20" x 1.18" / 115 x 56 x 30 mm
WEIGHT: 10.05 oz / 285 g (excluding battery)



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
SPOT LIGHT	TURBO	1000 Lumens	4 h	202 m
	HIGH	400 Lumens	6 h 30 min	124 m
	MED	130 Lumens	21 h	72 m
	LOW	30 Lumens	83 h	34 m
FLOOD LIGHT	TURBO	750 Lumens	4 h	61 m
	HIGH	400 Lumens	6 h	46 m
	MED	130 Lumens	23 h	27 m
	LOW	5 Lumens	400 h	7 m
SOS	130 Lumens	46 h	/	

HP25R Max 1000 Lumens
HIGH-PERFORMANCE
PROFESSIONAL
HEADLAMP

- Patented innovative lamp holder
- Micro rechargeable battery case
- Powered by a 18650 and compatible with two CR123A
- Separate battery case design
- Spot- and floodlights, 90° wide beam angle, 187 meters beam distance
- Dual switches for separate control

Technical innovation
patent number:
ZL 201020582158.1

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: Lamp head: 2.36" x 2.13" x 1.28" / 60 x 54 x 32.5 mm
Battery case: 3.25" x 1.97" x 1.38" / 82.5 x 50 x 35 mm
WEIGHT: 6.47 oz / 183.5 g (excluding battery)



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
SPOT LIGHT	TURBO	1000 Lumens	1 h 30 min	187 m
	HIGH	350 Lumens	4 h 30 min	109 m
	MED	130 Lumens	12 h	66 m
	LOW	30 Lumens	42 h	34 m
FLOOD LIGHT	HIGH	350 Lumens	2 h 30 min	44 m
	MED	130 Lumens	9 h	25 m
	LOW	30 Lumens	40 h	13 m
	ECO	4 Lumens	150 h	6 m
RED	0.2 Lumens	96 h	/	
RED FLASH	0.2 Lumens	192 h	/	

HP15 ULTIMATE EDITION Max 900 Lumens
HIGH-PERFORMANCE
RELIABLE HEADLAMP

- Patented drawer type battery case
- Dual switches for separate control
- Powered by 4 AA batteries
- Separate battery case design
- 900 lumens instant turbo

Technical innovation
patent number:
ZL 201120016782.X
ZL 201020582158.1

BATTERY: 4 x AA
SIZE: Lamp head: 2.65" x 2.20" x 1.37" / 67.4 x 55.9 x 34.7 mm
Battery case: 3.50" x 2.90" x 1.03" / 88.8 x 73.7 x 26.2 mm
WEIGHT: 5.44 oz / 154.2 g (excluding battery)



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Ni-MH Battery	Alkaline Battery	
TURBO	900 Lumens	/	/	178 m
HIGH	400 Lumens	3 h 30 min	3 h 10 min	119 m
MED	150 Lumens	10 h	8 h	73 m
LOW	50 Lumens	40 h	44 h	42 m
ECO	10 Lumens	160 h	170 h	19 m
STROBE	50 Lumens	/	/	/

HM65R Max 1400 Lumens
DUAL LIGHTING SOURCES
RELIABLE MAGNESIUM
HEADLAMP

- Patented sectional type circuit design
- Magnesium alloy lamp body
- Type-C charging
- Powered by a 18650 and compatible with two CR123A
- Dual switches for separate control

Technical innovation
patent number:
ZL 201420476030.5
ZL 201020582158.1
ZL 201420205409.7

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 3.11" x 2.05" x 1.54" / 79 x 52 x 39 mm
WEIGHT: 3.53 oz / 100 g (excluding battery)



Waterproof	IP68
Impact Resistance	2 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
SPOT LIGHT	TURBO	1000 Lumens	2 h	163 m
	HIGH	400 Lumens	22 h	101 m
	MED	130 Lumens	48 h	57 m
	LOW	50 Lumens	97 h	37 m
FLOOD LIGHT	HIGH	400 Lumens	21 h	55 m
	MED	130 Lumens	50 h	30 m
	LOW	8 Lumens	300 h	6 m



HM50R Max **500** Lumens
**RELIABLE COLD-RESISTANT
MULTIPURPOSE HEADLAMP**



- Black
- Camo color

NEW

- Patented sectional type circuit design
- Powered by a 16340 and compatible with two CR123A
- Detachable silicone lamp holder, can be used as a flashlight
- Handy and compact, sweat- channeling headband
- Two colors for option



Technical innovation patent number: ZL 201420205409.7

Waterproof	IP68
Impact Resistance	2 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		CR123A	16340	
TURBO	500 Lumens	2 h	2 h 30 min	80 m
HIGH	130 Lumens	14 h	10 h	42 m
MED	30 Lumens	48 h	24 h	20 m
LOW	4 Lumens	128 h	90 h	6 m

BATTERY: 1 x 16340 / 2 x CR123A
SIZE: 2.66" x 1.30" x 1.10" / 67.5 x 33 x 28 mm
WEIGHT: 2.22 oz / 63 g (excluding battery)

HM23 Max **240** Lumens
**RELIABLE LIGHTWEIGHT
HEADLAMP**

NEW

- Patented sectional type circuit design
- All-metal housing body
- Powered by one AA
- Anti-slip cleat design effectively fix the lamp
- Lockout function



Technical innovation patent number: ZL 201420205409.7

Waterproof	IP68
Impact Resistance	2 m, 6 times

BATTERY: 1 x AA
SIZE: 2.74" x 1.57" x 1.26" / 69.5 x 40 x 32 mm
WEIGHT: 2.05 oz / 58 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
HIGH	240 Lumens	8 h	55 m
MED	70 Lumens	16 h	30 m
ECO	4 Lumens	100 h	9 m

HL60R Max **950** Lumens
**DUAL LIGHT SOURCES RELIABLE
ALUMINUM HEADLAMP**

- Patented surrounded detachable lamp holder
- White and red lights
- Micro USB charging, powered by a 18650 and compatible with 2 CR123A
- Battery level indication
- All-metal housing - tough and reliable, two colors for option



Waterproof	IP68
Impact Resistance	2 m, 6 times

Technical innovation patent number: ZL 201420476030.5
ZL 201020582158.1

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 3.43" x 2.01" x 1.81" / 87 x 51 x 46 mm
WEIGHT: 4.27 oz / 121 g (excluding battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	950 Lumens	48 min	116 m
HIGH	400 Lumens	3 h	76 m
MED	150 Lumens	10 h	46 m
LOW	50 Lumens	29 h	27 m
ECO	5 Lumens	100 h	8 m
RED	1 Lumens	100 h	/

HL55 Max 900 Lumens
HIGH-PERFORMANCE
ALUMINUM HEADLAMP

- Patented surrounded detachable lamp holder
- Powered by a 18650 and compatible with two CR123A
- Handy and compact with high performance
- Sweat-channeling headband for more stable wear
- Instant Turbo



Waterproof	IP68
Impact Resistance	2 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO MODE	900 Lumens	/	116 m
HIGH	420 Lumens	3 h 45 min	79 m
MED	165 Lumens	10 h	50 m
LOW	55 Lumens	30 h	29 m
ECO	10 Lumens	150 h	12 m

Technical innovation patent number:
ZL 201020582158.1
ZL 201430091928.6

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 3.31" x 1.89" x 1.81" / 84 x 48 x 46 mm
WEIGHT: 4.06 oz / 115 g (excluding battery)

HL40R Max 600 Lumens
HIGH-PERFORMANCE
FOCUSING HEADLAMP

- Rotary focusing design for spot- and floodlights switching
- Micro USB charging
- Battery level indication
- Dual switches for separate control
- Overlapping reflective headband



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
			Flood Light	Spot Light
GENERAL MODE	TURBO	600 Lumens	1 h 20 min	43 m
	HIGH	300 Lumens	4 h 30 min	29 m
	MED	130 Lumens	11 h	19 m
	LOW	70 Lumens	22 h	14 m
	ECO	30 Lumens	50 h	9 m
FUNCTIONAL MODE	READ	4 Lumens	200 h	4 m
	SOS	30 Lumens	100 h	9 m

BATTERY: Built-in 2000mAh Li-ion battery pack
SIZE: 2.68" x 2.13" x 1.65" / 68 x 54 x 42 mm
WEIGHT: 4.02 oz / 114 g (including battery)

HL32R Max 600 Lumens
RECHARGEABLE
LIGHTWEIGHT TRAIL
RUNNING HEADLAMP

- Innovative patented lamp holder
- Wide-range floodlight; white and red lights
- Micro USB charging
- Reflective and sweat-channeling headband
- Dual switches - easy and fast operation



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

Technical innovation patent number:
ZL 201720607070.2
ZL 201730521452.9

BATTERY: Built-in 2000mAh Li-ion battery pack
SIZE: 2.52" x 1.81" x 1.48" / 64 x 46 x 37.5 mm
WEIGHT: 3.77 oz / 107 g (including battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
			Flood Light	Spot Light
GENERAL MODE	TURBO	600 Lumens	1 h	73 m
	TURBO	300 Lumens	4 h 30 min	49 m
	HIGH	130 Lumens	14 h	34 m
	MED	70 Lumens	24 h	23 m
	LOW	30 Lumens	60 h	16 m
FUNCTIONAL MODE	ECO	4 Lumens	200 h	7 m
	RED	1 Lumens	100 h	4 m
	SOS	30 Lumens	120 h	16 m
	RED FLASH	1 Lumens	200 h	4 m

HL30 Max 300 Lumens
DUAL LIGHT SOURCES
OUTDOOR HEADLAMP

- Innovative patented lamp holder
- Wide-range floodlight; white and red lights
- 2 AA batteries
- Dual switches - easy and fast operation
- Sweat-channeling reflective headband



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

Technical innovation patent number:
ZL 201720607070.2

BATTERY: 2 x AA
SIZE: 2.52" x 1.97" x 1.46" / 64 x 50 x 37 mm
WEIGHT: 2.57 oz / 73 g (excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME	DISTANCE	
			Flood Light	Spot Light
GENERAL MODE	TURBO	300 Lumens	4 h 30 min	50 m
	HIGH	130 Lumens	9 h	35 m
	MED	70 Lumens	41 h	23 m
	LOW	30 Lumens	71 h	16 m
	ECO	4 Lumens	200 h	6 m
FUNCTIONAL MODE	RED	1 Lumens	170 h	4 m
	SOS	30 Lumens	142 h	16 m
	RED FLASH	1 Lumens	340 h	4 m

HL26R

Max 450 Lumens

RECHARGEABLE LIGHTWEIGHT
TRAIL RUNNING HEADLAMP

- Ultra lightweight design
- Choice of spot- and floodlights
- Micro USB charging
- Battery level indication
- Sweat-channeling reflective headband



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
TURBO	450 Lumens	1 h 30 min		100 m
	130 Lumens	6 h		57 m
	70 Lumens	12 h		42 m
MED	30 Lumens	25 h		30 m
HIGH	40 Lumens	13 h		10 m
	4 Lumens	100 h		4 m
SOS	40 Lumens	26 h		/

BATTERY: Built-in 1600mAh Li-polymer battery
SIZE: 2.56" x 1.73" x 1.46" / 65 x 44 x 37 mm
WEIGHT: 3.03 oz / 86 g (including battery)

HL18R

Max 400 Lumens

RECHARGEABLE LIGHTWEIGHT
TRAIL RUNNING HEADLAMP

- Patented sectional type circuit design
- Three times injection molding process saves O-ring
- Dual separate switches for easy and fast operation
- 1300 mAh Li-polymer battery pack, compatible with 3 AAA batteries; Micro USB charging
- Ultralow standby current, reduces battery leakage with inserted cell



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1						
	MODE	OUTPUT	RUNTIME			DISTANCE
			Lithium	Pairdeer AAA	Sanyo AAA	
SPOT LIGHT	TURBO	400 Lumens	8 h 30 min	9 h	9 h	76 m
	HIGH	130 Lumens	12 h 30 min	14 h	14 h	40 m
	MED	70 Lumens	17 h 30 min	22 h	22 h	30 m
	LOW	30 Lumens	48 h	48 h	48 h	20 m
FLOOD LIGHT	HIGH	30 Lumens	54 h	56 h	56 h	10 m
	LOW	4 Lumens	145 h	150 h	150 h	5 m
	SOS	30 Lumens	72 h	80 h	80 h	6 m

Technical innovation
patent number:
ZL 201720607070.2
ZL 201420202409.7

BATTERY: 1300mAh Li-ion battery pack / 3 x AAA
SIZE: 2.27" x 1.67" x 1.46" / 57.7 x 42.3 x 37 mm
WEIGHT: 2.80 oz / 79.5 g (including headband and holder)

HL15

Max 200 Lumens

BATTERY REPLACEABLE,
LIGHTWEIGHT RUNNING
HEADLAMP

- Patented sectional type circuit design
- White and red lights; 100° wide-range floodlight
- Dual separate switches for easy and fast operation
- Sweat-channeling reflective headband
- 2 readily available AAA batteries



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		Ni-MH	Alkaline	
TURBO	200 Lumens	1 h 10 min	1 h 30 min	50 m
HIGH	70 Lumens	3 h 30 min	4 h	29 m
MED	30 Lumens	8 h 30 min	12 h 30 min	18 m
LOW	4 Lumens	37 h	58 h	8 m
ECO	0.2 Lumens	75 h	85 h	/
RED FLASH	0.2 Lumens	150 h	170 h	/

BATTERY: 2 x AAA
SIZE: 2.48" x 1.63" x 1.38" / 63 x 41.5 x 35 mm
WEIGHT: 2.12 oz / 60 g (excluding battery)

Technical innovation
patent number:
ZL 201720607070.2

HL12R

Max 400 Lumens

RECHARGEABLE ULTRA-LIGHT
RUNNING HEADLAMP

- Innovative patented lamp holder
- White and red lights
- Compact structure and light weight; sweat-channeling reflective headband
- Built-in 1000 mAh Li-polymer battery, micro USB charging; battery level indication
- Dual switches - easy and fast operation



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
	MODE	OUTPUT	RUNTIME	DISTANCE
GENERAL MODE	TURBO	400 Lumens	1 h	64 m
	HIGH	130 Lumens	8 h	36 m
	MED	70 Lumens	13 h	26 m
	LOW	30 Lumens	33 h	17 m
	ECO	4 Lumens	110 h	7 m
FUNCTIONAL MODE	RED	1 Lumens	40 h	3 m
	SOS	30 Lumens	66 h	17 m
	RED FLASH	1 Lumens	80 h	3 m

Technical innovation
patent number:
ZL 201720607070.2

BATTERY: Built-in 1000mAh Li-polymer battery
SIZE: 2.20" x 1.57" x 1.26" / 56 x 40 x 31.9 mm
WEIGHT: 2.57 oz / 73 g (including battery)

BICYCLE LIGHTS

Coming from a strong innovation background, Fenix's bicycle lights feature a Dual Distance Beam System, meaning they provide both close-up visibility and long-range illumination together with a board flood beam. With a user-friendly structural design, quality material and IP66 rated protection, Fenix bicycle lights are the rider's best choice, and ensure users a safe and excellent riding experience during night mountain cycling and road cycling.





BC35R Max 1800 Lumens

HIGH-PERFORMANCE CUT-OFF FACULA LINE BICYCLE LIGHT

Technical innovation
patent number:
ZL 201720600803.X

- Patented cut-off facula line won't dazzle oncoming passengers or vehicles
- Remote pressure switch - makes instant operation possible
- Intelligent anti-theft function
- Micro USB charging, convenient in every way
- OLED screen displays the current output and remaining battery level

BATTERY: Built-in two 18650 rechargeable Li-ion batteries
SIZE: 4.67" x 1.97" x 1.22" / 119 x 50 x 31 mm
WEIGHT: 9.98 oz / 283 g (including bike mount)



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
BURST	1800 Lumens	/	146 m
TURBO	1000 Lumens	2 h 12 min	119 m
HIGH	400 Lumens	6 h 30 min	73 m
MED	150 Lumens	12 h	45 m
LOW	45 Lumens	28 h	25 m
FLASH	150 Lumens & Side lights flicker alternately	/	/

BC30R Max 1800 Lumens

RECHARGEABLE DIGITAL OLED DISPLAY BICYCLE LIGHT

Technical innovation
patent number:
ZL 201220362988.2

- OLED screen displays the current output and remaining battery level
- Patented Dual Distance Beam System
- Remote pressure switch for easy and fast output selection
- Micro USB charging

BATTERY: Built-in 3.7V / 5200 mAh rechargeable battery
SIZE: 4.99" x 1.97" x 1.25" / 114 x 50 x 31.8 mm
WEIGHT: 5.68 oz / 221.6 g (excluding battery, bike mount)



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1800 Lumens	/	161 m
HIGH	1000 Lumens	2 h 40 min	122 m
MED	400 Lumens	7 h 20 min	76 m
LOW	150 Lumens	16 h 10 min	47 m
ECO	50 Lumens	36 h	28 m
FLASHING	150 Lumens	/	/



Best New Gear Award



Best in Show



ISPO Award Asian Products
Gold Winner 2015



Asia Outdoor Industry Award



BC30 Max 1800 Lumens

**BATTERY REPLACEABLE,
HIGH-PERFORMANCE
BICYCLE LIGHT**



- Battery replaceable
- 1800 lumens high output
- Dual Distance Beam System

Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1800 Lumens	/	170 m
HIGH	1200 Lumens	1 h 50 min	135 m
MED	500 Lumens	5 h	87 m
LOW	200 Lumens	11 h	56 m
ECO	100 Lumens	20 h	41 m
FLASH	200 Lumens	/	/

BATTERY: 2 x 18650 / 4 x CR123A
SIZE: 4.99" x 1.97" x 1.25" / 126.7 x 50 x 31.8 mm
WEIGHT: 5.68 oz / 161 g(excluding battery, bike mount)



BC25R Max 600 Lumens

**LIGHTWEIGHT CUT-OFF
FACULA LINE BICYCLE LIGHT**



Technical innovation
 patent number:
 ZL 201720600803.X

- Patented cut-off facula line won't dazzle oncoming passengers or vehicles
- Lightweight and compact
- Micro USB charging
- Battery level indication

Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	600 Lumens	2 h	106 m
HIGH	350 Lumens	7 h	79 m
MED	150 Lumens	15 h	53 m
LOW	50 Lumens	36 h	32 m
FLASH	150 Lumens	/	/

BATTERY: 2600 mAh Li-ion battery
SIZE: 4.45" x 1.26" x 1.22" / 113 x 32 x 31 mm
WEIGHT: 5.47 oz / 155 g(including bike mount)

NEW

BC21R **V2.0** Max 1000 Lumens
BATTERY REPLACEABLE,
LIGHTWEIGHT RECHARGEABLE
BICYCLE LIGHT

- Type-C charging
- Battery replaceable
- Quick-release bike mount
- Metal heat sink for better heat dissipation
- Patented Dual Distance Beam System



NEW

Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	1000 Lumens	2 h	145 m
HIGH	400 Lumens	6 h	90 m
MED	150 Lumens	13 h	50 m
LOW	50 Lumens	30 h	30 m
FLASH	400 Lumens&150 Lumens	/	/

BATTERY: 1 x 18650 / 2 x CR123A
SIZE: 4.57" x 1.22" x 1.18" / 116 x 31 x 30 mm
WEIGHT: 3.53 oz / 100 g(excluding battery)

BC05R Max 10 Lumens Red Light
RECHARGEABLE
MULTIPURPOSE
BICYCLE TAILLIGHT

- Multiple ways of wearing to serve as a headlamp, chest lamp and backpack light
- USB Type-C charging
- Compact and lightweight



NEW

Waterproof	IP66
Impact Resistance	1.5 m, 6 times



ANSI/PLATO FL1

MODE	OUTPUT	RUNTIME	DISTANCE
HIGH	10 Lumens	1 h 48 min	6 m
LOW	2 Lumens	10 h	
QUICK FLASH	2 Lumens	40 h	
SLOW FLASH	2 Lumens	72 h	

BATTERY: Built-in 300 mAh Li-polymer battery
SIZE: 2.01" x 0.87" x 0.83" / 51 x 22 x 21 mm
WEIGHT: 0.81 oz / 23 g(including bicycle mounting strap)



CAMPING LANTERN

Fenix's camping lanterns are all about innovation, and provide all-rounder performance. From the icy cold North Pole to the rain-soaked tropical forests, Fenix's all-weather waterproof lanterns provide thorough, uncompromising performance. Features listing from an exclusive dual-fuel battery compartment to multifaceted globe and a magnetic base, Fenix's camping lanterns keep your adventure going, anywhere, anytime!





CL30R Max 650 Lumens

WIDE-RANGE CHARGING AND DISCHARGING CAMPING LANTERN



- 35 meters beam diameter
- Micro USB charging and discharging function

Battery: One to three 18650 rechargeable Li-ion battery
Size: 5.35" x 3.66" x 3.66" / 136 x 93 x 93 mm
Weight: 14.53 oz / 412 g(excluding battery)

Iron grey Black

Waterproof	IP67
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		2600mAh	3500mAh	
TURBO	650 Lumens	4 h 30 min	6 h	35 m (Max)
HIGH	350 Lumens	9 h	12 h	
MED	100 Lumens	38 h	51 h	
LOW	50 Lumens	70 h	93 h	
ECO	10 Lumens	300 h	400 h	
FLASH MODE	100 Lumens	70 h	93 h	

CL26R Max 400 Lumens

HIGH-PERFORMANCE PORTABLE CAMPING LANTERN

- Patented multiple directional lighting for various scenes
- Micro USB charging
- Battery replaceable
- Powered by one 18650 or two CR123A batteries
- Top magnetic absorption, hanging loop and tripod socket for effective light fixation

Technical innovation
 patent number:
 ZL 2017215737626.X

Battery: 1 x 18650 / 2 x CR123A
Size: 3.82" x 1.93" x 1.93" / 97 x 49 x 49 mm
Weight: 3.99 oz / 113 g(excluding battery)



NEW

Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	400 Lumens	5 h	25 m (Max)
HIGH	150 Lumens	15 h	
MED	40 Lumens	30 h	
D-FRONT	30 Lumens	58 h	
D-UNDER	5 Lumens	240 h	
	30 Lumens	58 h	
RED	1.5 Lumens	200 h	
RED FLASH	1.5 Lumens	400 h	

CL23 Max 300 Lumens

3AA PORTABLE CAMPING LANTERN

- 3 AA readily available batteries
- Multiple directional lighting for various scenes
- Compact and lightweight
- Hanging loop and tripod socket for effective light fixation

Battery: One to three AA battery
Size: 3.35" x 2.17" x 2.17" / 85 x 55 x 55 mm
Weight: 4.94 oz / 140 g(excluding battery)



NEW

Waterproof	IP66
Impact Resistance	1.5 m, 6 times

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	300 Lumens	7 h 30min	20 m (Max)
HIGH	150 Lumens	13 h	
MED	40 Lumens	45 h	
D-FRONT	30 Lumens	80 h	
D-UNDER	5 Lumens	350 h	
	30 Lumens	80 h	
RED	1.5 Lumens	150 h	
RED FLASH	1.5 Lumens	300 h	

CL20R Max 300 Lumens

POCKET-SIZED
RECHARGEABLE
CAMPING LANTERN

- Micro USB charging
- 200 hours runtime
- Bottom magnetic absorption for effective light fixation



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

BATTERY: Built-in 1600 mah li-polymer battery
SIZE: 2.85" x 2.01" x 1.61" / 72.5 x 51 x 41 mm
WEIGHT: 3.21 oz / 91 g(including battery)

ANSI/PLATO FL1			
MODE	OUTPUT	RUNTIME	DISTANCE
TURBO	300 Lumens	6 h	20 m (Max)
HIGH	130 Lumens	12 h	
MED	40 Lumens	20 h	
LOW	1 Lumens	200 h	
RED	1.5 Lumens	100 h	
RED FLASH	1.5 Lumens	/	

CL09 Max 200 Lumens

MULTIFUNCTIONAL EDC
CAMPING LANTERN

- Compact and lightweight
- Included rechargeable Li-ion battery
- Multifunctional red and green signal lights
- Bottom magnetic absorption for effective light fixation



Waterproof	IP66
Impact Resistance	1.5 m, 6 times

BATTERY: 1 x ARB-L16-700U / 1 x 16340 / 1 x CR123A
SIZE: 3.09" x 0.87" x 0.87" / 78.5 x 22 x 22 mm
WEIGHT: 1.11 oz / 31.5 g(excluding battery)

ANSI/PLATO FL1				
MODE	OUTPUT	RUNTIME		DISTANCE
		ARB-L16-700U	CR123A	
TURBO	200 Lumens	2 h 40 min	6 h	10 m(Max)
HIGH	80 Lumens	5 h 40 min	19 h	
MED	30 Lumens	19 h 20 min	36 h	
LOW	1 Lumens	90 h	150 h	
RED	5 Lumens	30 h	48 h	
RED FLASH	5 Lumens	/	/	
GREEN	5 Lumens	48 h	76 h	



ACCESSORIES

Fenix has been striving, and succeeded to develop some creative accessories to enhance and dramatically improve the performance of flashlights, thus catering for various lighting demands.





Filter Adapter (AOF-S/S+/M/L)

This is a Fenix flashlight accessory with outstanding filtering ability to maintain strong red/blue/green light which can be used when signaling.

- Uses a toughened ultra-clear glass lens with anti-reflective coating that provide heat resistance and maximum light penetrability.
- Germany's Bayer PC 2805 material, aging and impact resistant.
- Anti-roll design, easy to assemble and disassemble.



Traffic Wand (AOT-01)

NEW

Compatible with Fenix TK35 series flashlight, this traffic wand can emits conspicuous orange light which features high visibility, is perfect for road and traffic guidance, SOS signal sending.

- German bayer PC2805 material.
- High compressive strength, impact resistance.
- High temperature resistance and benign thermal stability.
- Easy to assemble and disassemble.



Traffic Wand (AOT-S/M/L)

Fenix traffic wand can convert your flashlight into a glowing orange high-visibility wand. It's the best option for emergency situations and traffic control.

- German bayer PC2805 material
- High compressive strength, impact resistance
- High temperature resistance and benign thermal stability
- Easy to assemble and disassemble



Rechargeable Batteries

A protective circuit is built into the anode and covered with a riveted steel hat. The battery is fully covered with the steel shell, thus eliminating the potential risk of short circuiting caused by collision or impact.

- Triple overheat design, safe and reliable.
- Built-in overcharge and overdischarge protection circuit to ensure battery life.
- The circuit board is fully protected, with high reliability and impact resistance.

MODEL	TYPE	CAPACITY	VOLTAGE
ARB-L14-800	14500	800 mAh	3.6V
ARB-L14-1600U	14500+USB	1600 mAh	1.5V
ARB-L16-700	16340	700 mAh	3.6V
ARB-L16-700U	16340+USB	700 mAh	3.6V
ARB-L16-700UP	16340	700 mAh	3.6V
ARB-L18-2600	18650	2600 mAh	3.6V
ARB-L18-2600U	18650+USB	2600 mAh	3.6V
ARB-L18-2900	18650	2900 mAh	3.6V
ARB-L18-3400	18650	3400 mAh	3.6V
ARB-L18-3500	18650	3500 mAh	3.6V
ARB-L18-3500U	18650+USB	3500 mAh	3.6V
ARB-L18-2900L	18650	2900 mAh	3.6V
ARB-L21-5000	21700	5000 mAh	3.6V
ARB-L26-4500P	26650	4500 mAh	3.6V
ARB-L4-4800	26650	4800 mAh	3.6V



Dual Channels Multifunctional Charger (ARE-D2)

Fenix ARE-D2 is a dual channels smart charger that features charging and discharging function. It is compatible with types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays the charging, discharging and battery status clearly.

- Micro USB charging and USB discharging.
- LCD screen for battery level, charging and discharging status.
- 0.5/1.0/2.0A - three charging current for option.
- Rated output power: 3W (Ni-MH/Ni-Cd), 8.4W (Li-ion).
- Short circuit protection, over-current protection, over-voltage protection and reverse-polarity protection.

NEW



Single Channel Multifunctional Charger (ARE-D1)

Fenix ARE-D1 is a single channel smart charger that features charging and discharging function. It is compatible with types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays the charging, discharging and battery status clearly.

- Micro USB charging, and USB discharging.
- LCD screen for battery level, charging and discharging status.
- 0.5/1.0/2.0A - three charging current for option.
- Rated output power: 3W (Ni-MH/Ni-Cd), 8.4W (Li-ion).
- Short circuit protection, over-current protection, over-voltage protection and reverse-polarity protection.

NEW



Multifunctional Charger (ARE-A4)

Fenix ARE-A4 is a four channels smart charger, which is compatible with different types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays charging status and battery level clearly. In addition, a car charging mode offers high convenience for users.

- LCD display screen for charging and battery level.
- Compatible with different types of Li-ion and Ni-MH / Ni-Cd batteries.
- AC and DC charging modes.
- To charge the battery: 4.2V/1.0A (Li-ion), 1.5V/1.0A (Ni-MH/ Ni-Cd).
- Rated output power: 6W (Ni-MH/ Ni-Cd), 16.8W (Li-ion).
- Built-in short circuit protection, over current protection, over voltage protection and reverse polarity protection.

NEW



Dual Channels Charger (ARE-A2)

Fenix ARE-A2 is a dual channels charger, which is compatible with different types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays charging status and battery level clearly. In addition, a car charging mode offers high convenience for users.

- LCD display screen for charging and battery level.
- Compatible with different types of Li-ion and Ni-MH / Ni-Cd batteries.
- AC and DC charging modes.
- To charge the battery: 4.2V/1.0A (Li-ion), 1.5V/1.0A (Ni-MH/ Ni-Cd).
- Rated output power: 3W (Ni-MH/ Ni-Cd), 8.4W (Li-ion).
- Built-in short-circuit protection, over-current protection, over-voltage protection and reverse polarity protection.

NEW



Dual Channels Smart Charger (ARE-X2)

The Fenix ARE-X2 dual channels smart charger chooses the correct charging current for each battery inserted, for any battery between the 26650 and 10440. It also features micro USB charging and discharging, and LED charging/discharging indicators clearly inform you of the charging status.

- Compatible types of batteries.
- Micro USB charging, USB discharging.
- Be able to charge 2 same kind or different kinds of batteries simultaneously.
- Chooses corresponding charging mode depending on each type of battery.
- Built-in circuit protects batteries against overcharging, over-discharging, short circuiting and improper battery insertion.
- LED charging/discharging indicators.



Single Channel Smart Charger (ARE-X1)

The Fenix ARE-X1 is a single channel smart charger designed for 18650 and 26650 batteries, and provides charging, discharging and battery power detection.

- Compatible with one 18650 or one 26650 rechargeable Li-ion battery.
- Supports micro USB charging and USB discharging.
- LED charging/discharging indicator.
- LED battery power detection.
- Microcomputer chip controlled, digitally regulated charging to extend battery lifetime.
- Short circuit, overcurrent, overvoltage and reverse polarity protection.



ARE-X11 Charging Kit

The ARE-X11 is a compact and smart charger dedicated for 18650 Li-ion battery. It features USB charging and micro USB discharging function. Four LED lights clearly display the battery status, making the user aware of the status of charging/ discharging. Micro-computer chip controlled, digitally regulated charging extends battery life, and built-in multi-protection guarantees charging and discharging safety.

- 104 x 30 x 25mm.
- Weight: 30/41g (including/excluding protective cover, mini USB cable).
- Compatible battery: 18650 Li-ion battery.
- Charging: Micro USB charging port - DC 5V/1A from external power source, 4.2V/1A to charge the battery.
- Discharging: standard USB port, DC 5V/1A, maximum 2A.
- Made of high quality PC material and engineering plastic.
- Operating temperature : -20°C - 50°C .
- Operating humidity: 5%(0°C) - 90%(40°C).



Car Adapter (ARW-10)

Compatible with ARE-A4, ARE-A2.



Remote Pressure Switch (AER-01)

- Pressure pad switch (45 mm long) with a lifespan of 100,000 activations. Flashlight is activated by pressing any one of the three sensors.
- Cable is made from resilient PU material; coiled length 23cm, expanded length 80cm.
- The tail adapter is made from T6-grade aluminum with type III hard-anodized finish for durability and scratch resistance.
- Side switch on the tail adapter is capable of transmitting current of 1A for a long period of time, and is independent from the pressure pad switch.
- Waterproof to IPX8 standard.
- The tail adapter size: 25.4mm Diameter x 40 mm Length.
- Included: pressure pad switch, cable and tail adapter.
- Weight: 53.2 grams.



Remote Pressure Switch (AER-02)

- Noiseless (no click) pressure pad switch (30mm long) with a lifespan of 100,000 activations; capable of transmitting current of 3A for a long period of time.
- Tactical tail switch (round) - fully press for constant on; transmits 3A current for a long period of time.
- User-friendly Velcro design for fast and convenient operation.
- Cable made from resilient PU material, with a length of 24 cm.
- Tail adapter is made from T6-grade aluminum, type III hard-anodized and anti-abrasive finish.
- IP68 rated protection.
- Tail adapter size: 25.4mm Diameter x 31.5mm Length.
- Applicable flashlights: TK15UE, TK09 TAC (only High level), PD35 TAC, PD35, PD32, UC35.
- Included: pressure pad switch, coiled cable and tail adapter.
- Weight: 40 grams.



Remote Pressure Switch (AER-03)

- Applicable flashlights: TK20R (only on/off activation), TK32, TK16.
- Noiseless (no click) pressure pad switch for instant strobe and output selection; with a lifespan of 100,00 activations; capable of transmitting current of 3A for a long period of time.
- Tactical tail switch for constant/instant activation, and transmits 3A current for a long period of time.
- User-friendly Velcro design for fast and convenient operation.
- Cable made from resilient PU material, with a length of 24 cm.
- Tail adapter is made from T6-grade aluminum, type III hard-anodized and anti-abrasive finish.
- IP68 rated protection.
- Tail adapter size: 26.4mm Diameter x 32mm Length.
- Weight: 40 grams.



Helmet Attachment (ALG-03)

ALG-03 headlamp attachment is specifically designed for HL55 and HL60R fixation to outdoor or industrial work helmets. It enables easy and convenient attachment and detachment of headlamp to and from helmet, and allows adjustment of the lighting angle of the headlamps. In addition, it uses thickened blown-sponge, to fit to more helmets in various ways.

- Durable nylon material.
- 3M and TESA adhesive tapes are included.
- Easy attachment.



Helmet Attachment Hook Kit (ALD-02)

The ALD-02 helmet attachment hook set consists of four plastic hooks, which are designed to prevent the headband from slipping off the helmet.

- Environmentally friendly PC material.
- 4 helmet attachment hooks included.
- Applicable to helmet with thickness less than 6 mm.
- Not for fully protective helmets or helmets with foam lining.



Solar Power Charger (ARS-11)

- Eight American SUNPOWER solar panels.
- USB port, max 5V/0.5A.
- Desert digital camouflage 900D antique nylon fabric.
- Mobile phone bag, portable hanging buckle.
- Rated power: 12W.
- Size: 138 x 78 x 40mm.
- Weight: 380 grams.

NEW



Emergency Whistle (NW20)

Fenix turns a world of emergency preparedness experience with reliable lighting products into these high-output whistles. Whether injury, disaster or personal threats are present, the easy-blowing design takes 30% less effort to reach up to 120 decibels peak output. Pealess construction from food-grade stainless steel provides decades of confidence even in harsh outdoor environments.

- Easy-blowing design.
- Pealess construction.
- Up to 120 decibels peak output.
- Food-grade stainless steel.



Diffuser Tip (AOD-S / M / L)

Diffuser tips can soften the light and work as a camping light, signal light, reading light, tent light, etc.

- Durable, impact resistant and fireproof to V2 Standard.
- Easy operation.
- Imported novel optical material guarantees quality.



Rail Mount (ALG-01)

- Adjustable diameter design allows use with a wide range of flashlights.
- With plastic spacer - flashlights with diameter 23.6 mm - 24.2 mm can be fitted.
- Without plastic spacer - flashlights with diameter 25.4 mm-26.0 mm can be fitted.
- Quality aluminum in precision machining, anodized and power coated finish.
- Dedicated Allen wrench makes the flashlight clip lock the rail mount firmly.



Rail Mount (ALG-00)

ALG-00 features the quick detachable Picatinny rail design which suits for tactical firearms with fish oil Picatinny rails. The compatible flashlight diameter ranges from 22.5-26mm, and wrench is needed when clip flashlights. Full-metal housing made of durable aircraft-grade aluminum, and premium type III hard-anodized anti-abrasive finish in all black treatment without light reflection.



Quick-release Bike Mount (ALB-10)


Utilizing a unique split-type design for quick release of flashlights, the Fenix ALB-10 bicycle mount can effectively reduce the amount of steps and the time needed for mounting. Featuring Fenix's solidity and compatibility with a wide range of flashlights, this mount will ensure your safety during your night riding.

- Split-type design for quick release.
- Fits flashlights with diameter of 18mm - 26mm.
- Rotating 30 degree design adjusts to any locking angle.
- High-quality rubber mat provides shock-resistant and slip-resistant grip without scratching the handlebar.
- Anti-aging, solid and able to withstand extended exposure to sunlight and rain.



Multi-purpose Snap Hook (ALB-20)

- Quick release, stable wearing.
- Bottle opener.
- Straight screwdriver.
- Non-magnetizable.
- Size: 53.8 x 28.6 x 3.5mm.
- Weight: 9 g.
- Material: Titanium alloy TC4.



NEW

- Made of high-strength nylon cloth - light weight and wear resistant properties.
- Increased and large storage space, inner mesh cloth bag - enough for headlamp and battery storage.
- 50mm long lanyard.
- High-strength zipper.
- Applicable headlamps: HL10, HL12R, HL15, HL16, HL18R, HL23, HL26R, HL30, HL32R, HL35, HL40R, HL50, HM50R, HL55, HL60R.
- 1000 times cycle use; RoHS certificate; 1 year free repair, lifetime limited warranty.



MODEL	Filter Adapter			Diffuser Tip			Helmet light clip	Traffic Wand			Rechargeable Battery						Remote Switch	Rail Mount	Bike Mount	MODEL
	AOF			AOD			ALD	AOT			ARB									
	S	S+	M	L	S	M	L	04	S	M	L	01	L14 (USB)	L14 14500	L16 16340	L2 18650	L18 18650	L18 (USB)	L4 26650	
TK-SERIES																				
TK75																✓	✓			TK75
TK72R																				TK72R
TK65R																				TK65R
TK47																✓	✓			TK47
TK47UE																✓	✓			TK47UE
TK35												✓				✓	✓			TK35
TK35UE											✓	✓				✓	✓			TK35UE
TK32								✓								✓	✓	✓	✓	TK32
TK25R&B			✓			✓		✓			✓					✓	✓	✓	✓	TK25R&B
TK25RED			✓			✓		✓			✓					✓	✓	✓	✓	TK25RED
TK25UV			✓			✓		✓			✓					✓	✓	✓	✓	TK25UV
TK20R			✓			✓		✓			✓					✓	✓	✓	✓*	TK20R
TK16			✓			✓		✓			✓					✓	✓	✓	✓	TK16
TK15UE			✓			✓		✓			✓					✓	✓	✓	✓	TK15UE
PD-SERIES																				
PD40R			✓			✓					✓								✓	PD40R
PD35 TAC		✓			✓			✓			✓					✓	✓	✓	✓	PD35 TAC
PD35 V2.0		✓			✓			✓			✓					✓	✓	✓	✓	PD35 V2.0
PD32					✓			✓			✓					✓	✓	✓	✓	PD32
PD25	✓				✓			✓			✓				✓					PD25
LD-SERIES																				
LD42			✓			✓					✓									LD42
LD22	✓				✓			✓			✓					✓		✓	✓	LD22
LD15R								✓						✓						LD15R
LD12		✓			✓			✓			✓		✓							LD12
LD05 V2.0								✓												LD05 V2.0
LD02 V2.0								✓												LD02 V2.0
E-SERIES																				
E35UE					✓			✓			✓				✓	✓	✓	✓	✓	E35UE
E30R		✓			✓			✓			✓					✓	✓	✓	✓	E30R
E25UE		✓			✓			✓			✓		✓					✓	✓	E25UE
E18R		✓						✓						✓						E18R
E16Ti		✓						✓							✓					E16Ti
E16	✓							✓						✓						E16
E15								✓							✓					E15
E12								✓					✓							E12

FD-SERIES										FD-SERIES									
FD41		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	✓	FD41	Page 43		
FD30	✓		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	FD30	Page 32		
RC/UC-SERIES										RC/UC-SERIES									
RC40										RC40									
UC35 V2.0	✓		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	UC35 V2.0	Page 20		
UC30	✓		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	UC30	Page 32		
SD-SERIES										SD-SERIES									
SD20		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	✓	SD20	Page 39		
SD11	✓		✓		✓		✓		✓	✓	✓	✓	✓	✓	✓	SD11	Page 40		
LR-SERIES										LR-SERIES									
LR40R										LR40R									
HP-SERIES										HP-SERIES									
HP30R									✓	✓	✓	✓	✓	✓	✓	HP30R	Page 55		
HP25R									✓	✓	✓	✓	✓	✓	✓	HP25R	Page 55		
HP15UE								✓								HP15UE	Page 56		
HM-SERIES										HM-SERIES									
HM65R									✓	✓	✓	✓	✓	✓	✓	HM65R	Page 56		
HM50R								✓								HM50R	Page 57		
HL60R								✓	✓	✓	✓	✓	✓	✓	✓	HL60R	Page 58		
HL55								✓	✓	✓	✓	✓	✓	✓	✓	HL55	Page 59		
HM23								✓								HM23	Page 58		
HL-SERIES										HL-SERIES									
HL40R																HL40R	Page 59		
HL32R																HL32R	Page 60		
HL30								✓								HL30	Page 60		
HL26R								✓								HL26R	Page 61		
HL18R																HL18R	Page 61		
BIKE LIGHT										BIKE LIGHT									
BC35R																BC35R	Page 65		
BC30R																BC30R	Page 66		
BC25R																BC25R	Page 68		
BC30								✓	✓**	✓**	✓**	✓**	✓**	✓**	✓**	BC30	Page 67		
BC05R																BC05R	Page 69		
BC21R V2.0								✓	✓	✓	✓	✓	✓	✓	✓	BC21RV2.0	Page 69		
CAMP LANTERN										CAMP LANTERN									
CL30R										✓	✓	✓	✓	✓	✓	CL30R	Page 73		
CL26R								✓	✓	✓	✓	✓	✓	✓	✓	CL26R	Page 74		
CL20R																CL20R	Page 75		
CL09								✓								CL09	Page 75		

FENIX PRODUCTS SPECIFICATION CHART

MODEL	LED	Max output	Max runtime	Brightness	IP rating	Dimension	Weight	Battery	MODEL
TK-SERIES									
TK75	Cree XHP35 HI	5100 Lumens	95 h	6 Output levels	IP68	188×86×53mm	630g	4*18650	TK75 Page 48
TK72R	XHP70	9000 Lumens	88 h	Stepless regulation	IP68	156×64×50.5mm	420g	14000mAh rechargeable battery pack	TK72R Page 49
TK69R	Cree XHP70	3200 Lumens	113 h	5 Output levels	IP68	270.5×61.5×36.5mm	418g	10000mAh rechargeable battery pack	TK69R Page 13
TK47	Cree XHP35 HI	1300 Lumens	220 h	6 Output levels	IP68	266.2×61.5×28.6mm	376g	2*18650	TK47 Page 51
TK47UE	Cree XHP70	3200 Lumens	170 h	7 Output levels	IP68	266.2×61.5×28.6mm	365g	2*18650	TK47UE Page 52
TK35	Cree XHP35 HI(Neutral white)	1300 Lumens	235 h	5 Output levels	IP68	159.5×48×43mm	271g	2*18650	TK35 Page 15
TK35UE	Cree XHP 70	3200 Lumens	152 h	6 Output levels	IP68	164.5×48×43mm	286g	2*18650	TK35UE Page 14
TK32	Cree XP-L HI V3	1000 Lumens	170 h	8 Output levels	IP68	159.62×25mm	175g	2*CR123A/1*18650	TK32 Page 43
TK25 R&B	Cree XP-G2 S3 LED's & XP-E2 LED	1000 Lumens	110 h	7 Output levels	IP68	142.6×40×25.4mm	156.5g	2*CR123A/1*18650	TK25 R&B Page 44
TK25 Red	Cree XP-G2 S3 LED's & XP-E2 LED	1000 Lumens	110 h	7 Output levels	IP68	142.6×40×25.4mm	156.5g	2*CR123A/1*18650	TK25 Red Page 44
TK25UV	Cree XP-G2 LED	1000 Lumens	110 h	5 Output levels	IP68	142.6×40×25.4mm	156.5g	2*CR123A/1*18650	TK25 UV Page 16
TK20R	Cree XP-L HI V3	1000 Lumens	160 h	4 Output levels	IP68	151.5×34×25mm	141g	1*18650	TK20R Page 16
TK16	Cree XM-L2 U2	1000 Lumens	150 h	4 Output levels	IP68	140×34×25mm	122g	2*CR123A/1*18650	TK16 Page 18
TK15UE	Cree XPL HI V3	1000 Lumens	135 h	4 Output levels	IP68	142.5×34×25.4mm	141g	2*CR123A/1*18650	TK15UE Page 18
PD-SERIES									
PD40R	Cree XHP70	3000 Lumens	55 h	5 Output levels	IP68	138.5×34×30mm	126g	26650 rechargeable power battery	PD40R Page 20
PD35 TAC	Cree XP-L V5	1000 Lumens	140 h	5 Output levels	IP68	137×25.4×22.7mm	89g	2*CR123A/1*18650	PD35 TAC Page 22
PD35 V2.0	Cree XP-L HI V3 LED	1000 Lumens	430 h	5 Output levels	IP68	138×25.4×25.4mm	88g	2*CR123A/1*18650	PD35 V2.0 Page 21
PD32	Cree XP-L HI	900 Lumens	240 h	5 Output levels	IP68	129.5×24×22.6mm	77g	2*CR123A/1*18650	PD32 Page 24
PD25	Cree XP-L V5	550 Lumens	100 h	4 Output levels	IP68	93×21.5×21.5mm	47g	2*CR123A/1*18650	PD25 Page 24
LD-SERIES									
LD42	Cree XM-L2 U3 LED	1000 Lumens	400 h	4 Output levels	IP68	159.5×34×32.5mm	93g	4*AA	LD42 Page 29
LD22	Cree XP-G2 R5	300 Lumens	100 h	4 Output levels	IP68	155×21.5×18.3mm	72g	2*AA	LD22 Page 29
LD15R	XP-G3 (Neutral white)	500 Lumens	110 h	5 Output levels	IP68	70×22×19mm	40g	1*16340/1*CR123A	LD15R Page 30
LD12	Cree XP-G2 R5 (Neutral white)	320 Lumens	60 h	4 Output levels	IP68	102.5×21.5×20.5mm	56g	1*14500/1*AA	LD12 Page 30
LD05 V2.0	Cree XP-E2 R3	220 Lumens	58 h	3 Output levels	IP68	135×13.5×13.5mm	35g	1*14500/1*AA	LD05 V2.0 Page 31
LD02 V2.0	Cree XP-E2	100 Lumens	15 h	3 Output levels	IP68	92×13.5×13.5mm	16g	1*AAA	LD02 V2.0 Page 31
E-SERIES									
E35UE	Cree XM-L2 U2	1000 Lumens	150 h	5 Output levels	IP68	122×24×23mm	72g	2*CR123A/1*18650	E35UE Page 33
E30R	LUMINUS SST40	1500 Lumens	350 h	5 Output levels	IP68	98×25.4×21.5mm	51g	1*18650/2*CR123A	E30R Page 33
E25UE	Cree XP-L V5	1000 Lumens	100 h	5 Output levels	IP68	161×25.4×19.6mm	87g	2*14500/2*AA	E25UE Page 34
E18R	Cree XP-L HI LED	750 Lumens	70 h	4 Output levels	IP68	60×21×20mm	33.3g	1*16340/1*CR123A	E18R Page 34
E16TI	Cree XPL HI LED	650 Lumens	60 h	4 Output levels	IP68	51×20.9×19.7mm	25g	1*16340/1*CR123A	E16TI Page 35
E16	XP-L HI Neutral white	700 Lumens	75 h	4 Output levels	IP68	51×21.1×19.8mm	22g	1*ARB-L16-700P/1*CR123A	E16 Page 36
E15	Cree XP-G2 R5	450 Lumens	72 h	4 Output levels	IP68	64.8×22×19mm	29g	1*16340/1*CR123A	E15 Page 36
E12	Cree XP-E	130 Lumens	36 h	3 Output levels	IP68	90×19×19mm	28.5g	1*AA	E12 Page 37
E05	Cree XP-E2	85 Lumens	15 h	3 Output levels	IP68	66.5×15×15mm	12.5g	1*AAA	E05 Page 37
FD-SERIES									
FD41	Cree XP-L HI	900 Lumens	150 h	4 Output levels	IP68	146×40×25.4mm	160g	2*CR123A/1*18650	FD41 Page 43
FD30	Cree XP-L HI	900 Lumens	170 h	5 Output levels	IP68	140.5×25.4×23mm	96g	2*CR123A/1*18650	FD30 Page 32
RC/UC-SERIES									
RC40	Cree XM-L2 U2	6000 Lumens	125 h	5 Output levels	IP68	272×108×52mm	1234g	7800mAh/7.4v rechargeable battery	RC40 Page 47
UC35 V2.0	Cree XM-L2 U2	960 Lumens	150 h	5 Output levels	IP68	150×25.4×25.4mm	99g	1*18650/2*CR123A	UC35 V2.0 Page 20
UC30	Cree XP-L HI	1000 Lumens	170 h	5 Output levels	IP68	130×25.4×23.4mm	77g	1*18650/2*CR123A	UC30 Page 32
SD-SERIES									
SD20	Cree XM-L2 U2 & Cree XOE Red	1000 Lumens	7 h 30 min	3 Output levels	underwater 100m	208×40×26mm	245g	4*CR123A/2*18650	SD20 Page 39
SD11	Cree XM-L2 U2 (Neutral white)	1000 Lumens	3 h 40 min	3 Output levels	underwater 100m	138×34×26mm	132.5g	2*CR123A/1*18650	SD11 Page 40
LR-SERIES									
LR40R	Cree XP-L HI V3&XP-G3-S4	12000 Lumens	92 h 18 min	9 Output levels	IP68	154×80×51mm	500g	4*18650 Rechargeable Battery Pack	LR40R Page 52
HP-SERIES									
HP30R	Cree XM-L2&XP-G2 R5 LED(Neutral white)	1800 Lumens	400 h	8 Output levels	IP66	77×52×34mm	285g	2*18650/4*CR123A	HP30R Page 55
HP25R	Cree XM-L2 U2 & XP-G2 R5	1000 Lumens	150 h	8 Output levels	IP66	60×54×32.5mm	183.5g	1*18650/2*CR123A	HP25R Page 55
HP15UE	Cree XM-L2	900 Lumens	170 h	5 Output levels	IP66	67.4×55.9×34.7mm	154.2g	4*AA	HP15UE Page 56
HM-SERIES									
HM65R	XM-L2 U2, white, XP-G2 R5 Neutral white	1400 Lumens	300 h	8 Output levels	IP68	79×52×39mm	100g	1*18650/2*CR123A	HM65R Page 56
HM50R	Cree XM-L2 U2	500 Lumens	128 h	4 Output levels	IP68	67.5×33×28mm	63g	1*16340/1*CR123A	HM50R Page 57
HL60R	Cree XM-L2 T6 (Neutral white)	860 Lumens	100 h	6 Output levels	IP68	87×51×46mm	121g	1*18650/2*CR123A	HL60R Page 58
HL55	Cree XM-L2 T6 (Neutral white)	860 Lumens	100 h	5 Output levels	IP68	84×48×46mm	115g	2*CR123A/1*18650	HL55 Page 59
HM23	Cree XP-S3	150 Lumens	100 h	4 Output levels	IP68	71×42×32mm	68g	1*AA	HM23 Page 58
HL-SERIES									
HL40R	Cree XP-G3 S4	600 Lumens	300 h	4 Output levels	IP66	68×54×42mm	108g	Built-in 2000mAh Li-ion battery	HL40R Page 59
HL32R	XP-G3 S3 white	600 Lumens	200 h	6 Output levels	IP66	64×46×37.5mm	73.5g	Built-in 2000mAh Li-ion battery	HL32R Page 60
HL30	Cree XP-G3 S3	300 Lumens	200 h	6 Output levels	IP66	64×50×38mm	73g	2*AA	HL30 Page 60
HL26R	Cree XP-G2 R5	500 Lumens	150 h	6 Output levels	IP66	65×44×37mm	86g	Built-in 1600mAh Li-ion battery	HL26R Page 61
HL18R	Cree XP-G3 (Neutral white)	400 Lumens	150 h	7 Output levels	IP66	57.7×42.3×37mm	79.5g	1300mAh Li-ion battery/3*AAA	HL18R Page 61
HL15	Cree XP-G2 R5 (Neutral white)	200 Lumens	85 h	5 Output levels	IP67	63×41.5×35mm	60g	1*AA	HL15 Page 62
HL12R	Cree XP-G2 R5 (Neutral white)	400 Lumens	110 h	6 Output levels	IP66	54×40×31.9mm	73.3g	Built-in1000mAh Li-polymer battery	HL12R Page 62
BIKE LIGHT									
BC35R	XHP-50(Neutral white)	1800 Lumens	30 h	5 Output levels	IP66	119×50×31mm	283g	2*Rechargeable Li-ion battery	BC35R Page 65
BC30R	Cree XM-L2 U2 (Neutral white)	1800 Lumens	36 h	5 Output levels	IP66	114×50.5×31.8mm	221.6g	Built-in 5200mAh/3.7V rechargeable battery pack	BC30R Page 66
BC25R	XP-G3(Neutral white)	600 Lumens	36 h	4 Output levels	IP66	113×32×31mm	155g	2600mAh Li-ion battery	BC25R Page 78
BC30	Cree XM-L2 T6	1800 Lumens	20 h	5 Output levels	IP66	126.7×50×31.8mm	161g	2*18650/4*CR123A	BC30 Page 67
BC21R V2.0	XM-L2(Neutral white)	1000 Lumens	32 h	4 Output levels	IP66	116×31×30mm	100g	1*18650/2*CR123A	BC21R V2.0 Page 69
BC05R	Yi guang 2835 red	10 Lumens	41 h	4 Output levels	IP66	51×22×21mm	23g	140mAh Li-polymer battery	BC05R Page 69
CAMP LANTERN									
CL30R	Imported Premium Neutral White LED	650 Lumens	350 h	5 Output levels	IP67	136×93×93mm	412g	3*18650/6*CR123A	CL30R Page 73
CL26R	Imported Premium Neutral White LED	400 Lumens	400 h	6 Output levels	IP66	97×49×49mm	113g	1*18650/2*CR123A	CL26R Page 74
CL20R	Imported Premium Neutral White LED	300 Lumens	160 h	4 Output levels	IP66	72.5×51×41mm	91g	Built-in 1600mAh Li-ion battery	CL20R Page 75
CL23	Imported Premium Neutral White LED	300 Lumens	350 h	7 Output levels	IP66	85×55×55mm	140g	1-3*AA	CL23 Page 74
CL09	Imported Premium Neutral White LED	200 Lumens	150 h	6 Output levels	IP68	78.5×22×22mm	31.5g	1*16340/1*CR123A	CL09 Page 75

CUSTOMER SERVICE

Fenix will exert every effort possible to make the service experience for our consumers as memorable, painless and cheerful as possible.

Fenix is concerned about your problems and difficulties when you are using our products, and we will try our best to provide excellent all-round service and support to you via our official website, Customer Service e-mail service and our survey questionnaire.

Fenix Product Warranty Terms

1.Service Principle

- a) Fenix provides easy, reliable, speedy service to all lights under our warranty.
- b) Dealers will be responsible for customers’ complaints. Customers should contact the dealer/distributor from where they bought their Fenix lights, for warranty support, with their Fenixlight Limited’s “Warranty Card”, or a trade invoice or receipt. Fenix will provide our authorized dealers with the necessary technology and parts to service/repair our lights.

2.Warranty Details

- a) 15 days free replacement. Fenix will replace a new product if within 15 days of purchase, any manufacturing defect causes a malfunction during normal use, with the same model. If the model has been discontinued, customer will receive a model with similar specifications, or an improved model.
- b) 5 years free repairs. Fenix offers free repairs for lights for 5 years after date of purchase, if a problem occurs during normal use. Different warranty period for different products:

Type	Warranty
Flashlight, headlamp, bicycle light and camping lantern (including rechargeable lights but not with built-in battery)	5 years (rechargeable battery excluded)
Flashlight, headlamp, bike light and camping lantern (with built-in battery)	2 years (battery included)
Rechargeable battery, battery charger, bike mount and remote pressure switch	1 year

Fenix products and free offers, except for these listed above, are not covered under the Fenix product warranty.

- c) Limited Lifetime Warranty. For light repairs after expiration of the 5 year free repair warranty period, your light will be repaired but you will be charged for parts. The distributor will provide you with a quote before repairs.
- d) Extended Warranty Service. Fenix recommends that customers register their products with the serial number on the official Fenix website: www.fenixlight.com or Fenix WeChat account. Upon successful registration customers will receive an extra six (6) months warranty service.
- e) Warranty Certificate. Customers requesting aftersales service from Fenix distributors or dealers, should present their completed Fenix Warranty Card, purchase invoice or receipt. The distributor should then provide service to the customer/s, and Fenix will support backup for this service.
- f) The free warranty does not cover any damage or failure caused by:
 - i. Normal wear and tear;
 - ii. Rough operation;
 - iii. Battery leakage;
 - iv. Any defect or damage caused by improper operation, including but not limited to, operation which does not comply with the warranty or operator’s manual specifications, e.g. if the operator’s manual warns you against disassembling the flashlight head, doing so may damage the flashlight head and will void the warranty.
 - v. Any damage or defect caused by behavior beyond Fenix’s control.
- g) To claim against your product warranty, contact our warranty service department with the following information:
 - i. Name;
 - ii. Type and model of product claimed for;
 - iii. Serial number;
 - iv. Age of the product;
 - v. Description of the problem.

NOTE: This new policy is only valid for flashlights purchased since 01 January 2015.

For any problems/suggestions, please email our Customer Service Department:

service@fenixlight.com (Europe/America regions)
service_1@fenixlight.com (Asia/Oceania/Africa regions)
Tel: +86 400 8866 093 +86 755 2963 1193

www.fenixlight.com

PHOTOS TAKEN

- Cover: Brendon Wainwright
- Back Cover: Scott Wesson & Jason Frankle
- Inside Front Corner: Carlos Serrano
- Inside Back Cover: Chaoyang Li
- Illustration: Carlos Serrano
 - Brendon Wainwright
 - Samhū
 - Oldrich Oimer
 - Jeff Nass
 - Zorin Denu

