

Samsung DVM S Series Multiposition Air Handler Unit

Job Name _____
Purchaser _____
Submitted to _____
Unit Designation _____

Location _____
Engineer _____
Reference _____ Approval _____ Construction _____
Schedule # _____

Specifications

Performance	Nominal Capacity (Btu/h)	Cooling	24,000
		Heating	27,000
Power	Voltage	ø / V / Hz	1 / 208-230 / 60
	Nominal Input Current*	Cooling (A)	1.12
	MCA*	Amps	0.9
	MOCP*	Amps	10
Fan	Type	Double-inlet, forward curve, centrifugal	
	Motor	Type	Constant-torque (ECM)
		HP	1/3
		Output (W)	290
Airflow	CFM @ 0.4" ESP (UL)	L / M / H	450 / 560 / 706
External Static Pressure	Standard	"WC	0.4
	Min. / Max.	"WC	0.1 / 0.7
Refrigerant	Type	R410A	
	Control Method	Electronic Expansion Valve	
Piping Connections	Liquid	Inches	3/8
	Suction	Inches	5/8
	Drain	Inches	3/4" FNPT
Unit Dimensions	W X H X D	Inches	17 1/2 X 43 X 21
	Weight	lbs.	109
Sound Level	Low / Mid / High	dB(A)	37 / 39 / 43
Accessories	Filter Base W/1" Filter		VFB-1
	External Temperature Sensor		MRW-TA
	Supplemental Electric Heater Kit	3Kw	VHK-103A
		5Kw	VHK-105A
		10Kw	VHK-110A
	Downflow Conversion Kit		VDK-1
	EEV Extension Wire Harness**		DB82-05832A
	External Contact Control		MIM-B14
Safety Certifications	CN83 Pigtail (for external contact input)		DB39-01263A
			ETL (UL 1995)

*Power data is without optional electric heat kits installed.

**Required for applicable models when using Downflow Conversion Kit

¹ Nominal cooling capacities are based on: Indoor temperature: 80 °F DB, 67°F WB. Outdoor temperature: 95°F DB, 75°F WB.

Nominal heating capacities are based on: Indoor temperature: 70 °F DB, 60°F WB. Outdoor temperature: 47°F DB, 43°F WB.

² Refer to technical data book for fan performance details and settings

Samsung HVAC maintains a policy of ongoing development, specifications are subject to change without notice.



- Compatible with Samsung DVM S, DVM S Water, and DVM Eco systems (AM*****AA).
- High-voltage terminal block temperature sensor to disable unit in the event overheating of controls power connection.
- Multiposition - vertical, horizontal left, and horizontal right.
- Capable of being field convertible to downflow configuration with optional downflow conversion kit.
- Air handler has an air leakage of no more than 2 percent of the design air flow rate when tested in accordance with ASHRAE 193.

Construction

The unit shall be constructed of insulated, powder coated, galvanized steel

Heat Exchanger

The heat exchanger shall be mechanically bonded fin to copper tube

Indoor Fan

Indoor fan is a double-inlet, forward curve, centrifugal type with a single constant-torque (ECM) fan motor

The indoor unit shall have low, medium, high, and auto fan speed setting options.

Five fan speed taps for optional air flow setting during installation

The indoor unit shall have the capability to turn the fan off in heating or cooling modes while in thermal-OFF status (external sensor required).

Controls

0 volt ON/OFF control (ex: auxiliary drain switch) when using the optional CN83 pigtail (part number DB39-01263A, sold separately).

The indoor unit shall integrate with the Samsung NASA Controls Network Solution

Controls shall integrate with a BMS system

Control wiring shall be 2 X 16 AWG shielded wire

Air Filtration

Air filtration must be field provided

Samsung DVM S Series Multiposition Air Handler Unit
Dimensional Data

No.	Description
①	Gas Pipe
②	Liquid Pipe
③	Drain Connection
④	Air Outlet
⑤	Air Inlet

